

Package ‘ASpli’

April 15, 2020

Type Package

Title Analysis of alternative splicing using RNA-Seq

Version 1.12.0

Date 2017-10-12

Author Estefania Mancini, Javier Iserte, Marcelo Yanovsky and Ariel Chernomoretz

License GPL

biocViews ImmunoOncology, GeneExpression, Transcription,
AlternativeSplicing, Coverage, DifferentialExpression,
DifferentialSplicing, TimeCourse, RNASeq, GenomeAnnotation,
Sequencing, Alignment

Depends methods, grDevices, stats, utils, parallel, edgeR

Imports GenomicRanges, GenomicFeatures, BiocGenerics, IRanges,
GenomicAlignments, Gviz, S4Vectors, AnnotationDbi, Rsamtools,
BiocStyle

Maintainer Estefania Mancini <emancini@leloir.org.ar>

Description Integrative pipeline for the analysis of alternative
splicing using RNAseq.

git_url <https://git.bioconductor.org/packages/ASpli>

git_branch RELEASE_3_10

git_last_commit 23929ac

git_last_commit_date 2019-10-29

Date/Publication 2020-04-14

R topics documented:

| | |
|-------------------------------|----|
| ASpli-package | 2 |
| AS accessors | 4 |
| AsDiscover | 5 |
| ASpliAS-class | 6 |
| ASpliCounts | 7 |
| ASpliCounts-class | 8 |
| ASpliDU-class | 9 |
| ASpliFeatures-class | 9 |
| binGenome | 10 |
| binGenome-methods | 11 |

| | |
|-----------------------------------|----|
| Counts accesors | 12 |
| DU accesors | 13 |
| DUreport | 14 |
| DUreportBinSplice | 16 |
| Examine ASpliDU objects | 18 |
| Example data | 19 |
| Features accesors | 20 |
| filterDU | 21 |
| getConditions | 23 |
| junctionDUreport | 24 |
| loadBAM | 26 |
| mergeBinDUAS | 27 |
| plotBins | 28 |
| plotGenomicRegions | 31 |
| rds | 34 |
| readCounts | 36 |
| show-methods | 37 |
| Subset ASpli objects | 37 |
| write | 39 |
| write-methods | 40 |

| | |
|--------------|-----------|
| Index | 41 |
|--------------|-----------|

ASpli-package

Analysis of alternative splicing using RNAseq

Description

ASpli is an integrative and flexible package that facilitates the characterization of genome-wide changes in AS under different experimental conditions. ASpli analyzes the differential usage of introns, exons, and splice junctions using read counts, and estimates the magnitude of changes in AS by calculating differences in the percentage of exon inclusion or intron retention using splice junctions. This integrative approach allows the identification of changes in both annotated and novel AS events.

ASpli allows users to produce self-explanatory intermediate outputs, based on the aim of their analysis. A typical workflow involves parsing the genome annotation into new features called bins, overlapping read alignments against those bins, and inferring differential bin usage based on the number of reads aligning to the bins and junctions.

Details

Package: ASpli

Type: Package

Version: 1.5.1

Date: 2018-02-22

License: GPL

Depends: methods, GenomicRanges, GenomicFeatures, edgeR, methods, BiocGenerics, IRanges, GenomicAlignments,

Author(s)

Estefania Mancini, Javier Iserte, Marcelo Yanovsky and Ariel Chernomoretz

References

- Acute effects of light on alternative splicing in light-grown plants. *Photochemistry and Photobiology*. Mancini, E, Sanchez, S, Romanowsky, A, Yanovsky, MJ. DOI: 10.1111/php.12550
- GEMIN2 attenuates the effects of temperature on alternative splicing and circadian rhythms in *Arabidopsis thaliana*. *Proceedings of the National Academy of Sciences*. Schlaen, RG, Mancini, E, Sanchez, SE, Perez-Santangelo, S, Rugnone, ML, Simpson, CG, Brown, JWS, Zhang, X, Chernomoretz, A, Yanovsky, MJ. DOI:10.1073/pnas.1504541112
- Genome wide comparative analysis of the effects of PRMT5 and PRMT4/CARM1 arginine methyltransferases on the *Arabidopsis thaliana* transcriptome. *BMC Genomics*. Hernando, E, Sanchez, S, Mancini, E, Yanovsky MJ. DOI:10.1186/s12864-015-1399-2
- A role for LSM genes in the regulation of circadian rhythms. *Proceedings of the National Academy of Sciences*. Perez Santangelo, S, Mancini, E, Francey, LJ, Schlaen, RG, Chernomoretz, A, Hogenesch, JB, Yanovsky MJ. DOI: 10.1073/pnas.1409791111
- The dengue virus NS5 protein intrudes in the cellular spliceosome and modulates splicing. *PLOS Pathogens*. De Maio, F, Risso, G, Iglesias, G, Shah, P, Pozzi, B, Gebhard, L, Mammi, L, Mancini, E, Yanovsky, M, Andino, R, Krogan, N, Srebrow, A and Gamarnik, A. DOI:10.1371/journal.ppat.1005841

Examples

```
# Create a transcript DB from gff/gtf annotation file.
# Warnings in this examples can be ignored.
library(GenomicFeatures)
genomeTxDb <- makeTxDbFromGFF( system.file('extdata','genes.mini.gtf',
                                         package="ASpli") )

# Create an ASpliFeatures object from TxDb
features <- binGenome( genomeTxDb )

# Define bam files, sample names and experimental factors for targets.
bamFileNames <- c( "A_C_0.bam", "A_C_1.bam", "A_C_2.bam",
                  "A_D_0.bam", "A_D_1.bam", "A_D_2.bam" )
targets <- data.frame(
  row.names = paste0('Sample_',c(1:6)),
  bam = system.file( 'extdata', bamFileNames, package="ASpli" ),
  factor1 = c( 'C', 'C', 'C', 'D', 'D', 'D' ) )

# Load reads from bam files
bams <- loadBAM( targets )

# Read counts from bam files
counts <- readCounts( features, bams, targets, cores = 1, readLength = 100,
                    maxISize = 50000 )

# Calculate differential usage of genes, bins and junctions
du <- DUreport( counts, targets )
du <- junctionDUreport( counts, targets, appendTo = du )

# Calculate PSI / PIR for bins and junction.
```

```
as      <- AsDiscover( counts, targets, features, bams, readLength = 100,
                      threshold = 5, cores = 1 )
```

AS accessors

Accessors for ASpliAS object

Description

Methods to retrieve and set data in ASpliAS object. Setting data into an ASpliAS object is not a typical task and must be done with care, because it can affect the integrity of the object.

Usage

```
altPSI( x )
esPSI( x )
irPIR( x )
joint( x )
junctionsPIR( x )
junctionsPSI( x )
```

Arguments

x An ASpliAS object

Value

Returns dataframes with genomic metadata and PSI and PIR metrics

Author(s)

Estefania Mancini, Marcelo Yanovsky, Ariel Chernomoretz

Examples

```
# Accessing data tables from an ASpliAS object

as <- aspliASexample()

ap <- altPSI(as)
ep <- esPSI(as)
ip <- irPIR(as)
j  <- joint(as)
jpi <- junctionsPIR(as)
jps <- junctionsPSI(as)

# Setting data tables to an ASpliAS object

as2 <- new( 'ASpliAS' )

altPSI( as2 ) <- ap
esPSI( as2 ) <- ep
irPIR( as2 ) <- ip
joint( as2 ) <- j
```

```
junctionsPIR( as2 ) <- jpi
junctionsPSI( as2 ) <- jps
```

AsDiscover

Report PSI and PIR using experimental junctions

Description

Given a bin, it is possible to calculate PSI/PIR metric using junctions to estimate changes in the use of it along different conditions. PSI or PIR metric is calculated for each bin and experimental condition. The selection of which metric is used is based on the kind of splicing event associated with each bin.

Usage

```
AsDiscover( counts, targets, features, bam, readLength, threshold , cores )
```

Arguments

| | |
|------------|---|
| counts | An object of class ASpliCounts. |
| targets | A dataframe containing sample, bam and experimental factors as columns and samples as rows. |
| features | An object of class ASpliFeatures. |
| bam | A list with BAM files contents. |
| readLength | Read length of sequenced read. Default 100L |
| threshold | Minimum number of reads supporting junctions. Default=5 |
| cores | Number of processing cores to use |

Value

An object of class ASpliAS

| | |
|--------------|--|
| irPIR | reports: event, eli counts (J1), ie1 counts (J2), j_within (J3), PIR by condition. J1, J2, J3 sum of junctions (J1, J2, J3) by condition. |
| altPSI | reports: event, J1 (start), J2 (end), J3 (exclusion), PSI. J1, J2, J3 sum of junctions (J1, J2, J3) by condition. |
| esPSI | reports: event, J1 (start), J2 (end), J3 (exclusion), PSI. J1, J2, J3 sum of junctions (J1, J2, J3) by condition. |
| junctionsPIR | PIR metric for each experimental junction using eli and ie2 counts. Exclusion junction is the junction itself. This output helps to discover new introns as well as new retention events. |
| junctionsPSI | Given a junction, it is possible to analyze if it shares start, end or both with another junction. If so, is because there is more than one way for/of splicing. Ratio between them along samples is reported. |

Author(s)

Estefania Mancini, Marcelo Yanovsky and Ariel Chernomoretz

See Also

Accessors: [irPIR](#), [altPSI](#), [esPSI](#), [junctionsPIR](#), [junctionsPSI](#)

Export: [writeAS](#)

Examples

```
# Create a transcript DB from gff/gtf annotation file.
# Warnings in this examples can be ignored.
library(GenomicFeatures)
genomeTxDb <- makeTxDbFromGFF( system.file('extdata','genes.mini.gtf',
                                         package="ASpli") )

# Create an ASpliFeatures object from TxDb
features <- binGenome( genomeTxDb )

# Define bam files, sample names and experimental factors for targets.
bamFileNames <- c( "A_C_0.bam", "A_C_1.bam", "A_C_2.bam",
                  "A_D_0.bam", "A_D_1.bam", "A_D_2.bam" )
targets <- data.frame(
  row.names = paste0('Sample_',c(1:6)),
  bam = system.file( 'extdata', bamFileNames, package="ASpli" ),
  factor1 = c( 'C','C','C','D','D','D' ) )

# Load reads from bam files
bams <- loadBAM( targets )

# Read counts from bam files
counts <- readCounts( features, bams, targets, cores = 1, readLength = 100,
                    maxISize = 50000 )

# Calculate differential usage of genes, bins and junctions
du <- DUreport( counts, targets )
du <- junctionDUreport( counts, targets, appendTo = du)

# Calculate PSI / PIR for bins and junction.
as <- AsDiscover( counts, targets, features, bams, readLength = 100,
                threshold = 5, cores = 1 )

writeAS( as = as, output.dir = "only_as" )
```

ASpliAS-class

Class "ASpliAS"

Description

Results of PSI and PIR using experimental junctions

Slots

irPIR: Reports: event, e1i counts (J1), ie1 counts (J2), j_within (J3), PIR by condition. J1, J2, J3 sum of junctions (J1, J2, J3) by condition.

altPSI: Reports: event, J1 (start), J2 (end), J3 (exclusion), PSI. J1, J2, J3 sum of junctions (J1, J2, J3) by condition.

esPSI: Reports: event, J1 (start), J2 (end), J3 (exclusion), PSI. J1, J2, J3 sum of junctions (J1, J2, J3) by condition.

joint: It is a combination of irPIR, altPSI and esPSI tables

junctionsPIR: PIR metric for each experimental junction using e1i and ie2 counts. Exclusion junction is the junction itself. This output helps to discover new introns as well as new retention events

junctionsPSI: Given a junction, it is possible to analyze if it shares start, end or both with another junction. If so, is because there is more than one way for/of splicing. Ratio between them along samples is reported.

Author(s)

Estefania Mancini, Javier Iserte, Marcelo Yanovsky, Ariel Chernomoretz

See Also

Methods: [AsDiscover](#)

Accessors: [altPSI](#), [irPIR](#), [esPSI](#), [joint](#), [junctionsPIR](#), [junctionsPSI](#)

ASpliCounts

Class "ASpliCounts"

Description

Contains results of read overlaps against all feature levels summarization

Slots

gene.counts

exon.intron.counts

junction.counts

e1i.counts

ie2.counts

gene.rd

bin.rd

Author(s)

Estefania Mancini, Javier Iserte, Marcelo Yanovsky, Ariel Chernomoretz

ASpliCounts-class *Class "ASpliCounts"*

Description

Contains results of read overlaps against all feature levels summarization

Slots

gene.counts: Object of class "data.frame"
exon.intron.counts: Object of class "data.frame"
junction.counts: Object of class "data.frame"
eli.counts: Object of class "data.frame"
ie2.counts: Object of class "data.frame"
gene.rd: Object of class "data.frame"
bin.rd: Object of class "data.frame"

Methods

AsDiscover psi and pir metrics
countsb bin counts accesor
countse1i eli counts accesor
countsg gene counts accesor
countsie2 ie2 counts accesor
countsj junction counts accesor
DUreport_DEXSeq differential expression and usage estimation using DEXSeq
DUreport differential expression and usage estimation using DEXSeq
rdsb bin read densities accesor
rdsg gen read densities accesor
rds compute read densities on genes and bins
writeCounts Export count tables
writeRds Export read density tables

Author(s)

Estefania Mancini, Javier Iserte, Marcelo Yanovsky, Ariel Chernomoretz

| | |
|---------------|-----------------|
| ASpliDU-class | Class "ASpliDU" |
|---------------|-----------------|

Description

Contains results of differential expression at gene level and differential usage at bin and junction level estimation using DEreport method.

Slots

genes

bins

junctions

Author(s)

Estefania Mancini, Javier Iserte, Marcelo Yanovsky, Ariel Chernomoretz

| | |
|---------------------|-----------------------|
| ASpliFeatures-class | Class "ASpliFeatures" |
|---------------------|-----------------------|

Description

Contains Genomic Ranges of different features extracted from a TxDb

Slots

genes:

bins:

junctions:

Author(s)

Estefania Mancini, Javier Iserte, Marcelo Yanovsky, Ariel Chernomoretz

binGenome

*Feature coordinates extraction***Description**

Exons and introns are subdivided into new features called exon and intron bins and are then classified into exclusively exonic bins, exclusively intronic bins or alternative splicing (AS) bins .

Usage

```
binGenome(genome, geneSymbols, logTo = "ASpli_binFeatures.log" )
```

Arguments

| | |
|-------------|--|
| genome | An object of class transcriptDb (TxDb) |
| geneSymbols | A dataframe with symbol (common names) of TxDb genes. If geneSymbols is NULL, gene name will be repeated |
| logTo | Filename where to print features extraction log |

Details

Exon and intron coordinates are extracted from gene annotation, only those from multi-exonic genes are saved for further evaluation. In case more than one isoform exist, some exons and introns will overlap. Exons and introns are then disjoint into new features called exon and intron bins, and then they are classified into exclusively exonic bins, exclusively intronic bin or alternative splicing bins (AS-bins), which are labeled according to which alternative splicing event are assumed to come from:

- ES: exon skipping
- IR: intron retention
- Alt5|3'ss: alternative five/three prime splicing site
- "*" (ES*, IR*, AltSS*) means this AS bin/region is involved simultaneously in more than one AS event type
- external: from the beginning or the end of a transcript

Subgenic features are labeled as follow (hypothetical GeneAAA):

- GeneAAA:E001: defines first exonic bin
- GeneAAA:I001: defines first intronic bin
- GeneAAA:Io001: defines first intron before disjoint into bins
- GeneAAA:J001: defines first junction

Junctions are defined as the last position of five prime exon (donor position) and first position of three prime exon (acceptor position). Using TxDb object, it is possible to extract annotated/known junctions. This information will be useful for the analysis of "experimental" junctions (reads aligned with gaps). Bins and junctions are labelled always in 5' to 3' sense. This notation is strand independent. It implies that bin / junction with lower numbering is always at 5'.

Value

An ASpliFeatures object. It is a list of features using GRanges format.

Author(s)

Estefania Mancini, Javier Iserte, Marcelo Yanovsky, Ariel Chernomoretz

See Also

[featuresg](#), [featuresb](#), [featuresj](#)

Examples

```
# Create a transcript DB from gff/gtf annotation file.
# Warnings in this examples can be ignored.
library(GenomicFeatures)
genomeTxDb <- makeTxDbFromGFF( system.file('extdata', 'genes.mini.gtf',
                                         package="ASpli") )

# Create an ASpliFeatures object from TxDb
features <- binGenome( genomeTxDb )

# Extract gene, bin and junctions features
GeneCoord <- featuresg(features)
BinCoord <- featuresb(features)
JunctionCoord <- featuresj(features)
```

binGenome-methods

Feature coordinates extraction

Description

Feature coordinates extraction from a Transcript Database

Methods

`signature(genome = "TxDb")` An object of class transcriptDb (TxDb)

Author(s)

Estefania Mancini, Javier Iserte, Marcelo Yanovsky, Ariel Chernomoretz

See Also

[featuresg](#), [featuresb](#) , [featuresj](#)

Description

Accessors for ASpliCounts object

Usage

```
countsb(x)
countse1i(x)
countsg(x)
countsie2(x)
countsj(x)
rdsg(x)
rdsb(x)
```

Arguments

x An ASpliCounts object

Value

Returns dataframes with counts by sample and genomic metadata

Author(s)

Estefania Mancini, Marcelo Yanovsky, Ariel Chernomoretz

Examples

```
# Get data tables from an ASpliCounts object

counts <- aspliCountsExample()

cb1 <- countsb(counts)
ce1i <- countse1i(counts)
cg <- countsg(counts)
cie2 <- countsie2(counts)
cj <- countsj(counts)
rg <- rdsg(counts)
rb <- rdsb(counts)

# Set data tables to an ASpliCounts object

countsb(counts) <- cb1
countse1i(counts) <- ce1i
countsg(counts) <- cg
countsie2(counts) <- cie2
countsj(counts) <- cj
rdsg(counts) <- rg
rdsb(counts) <- rb
```

| | |
|--------------|-------------------------------------|
| DU accessors | <i>Accessors for ASpliDU object</i> |
|--------------|-------------------------------------|

Description

Accessors for ASpliDU object

Usage

```
genesDE( x )  
binsDU( x )  
junctionsDU( x )
```

Arguments

x An ASpliDU object

Value

Returns dataframes with genomic metadata and logFC and pvalue

Author(s)

Estefania Mancini, Javier Iserte, Marcelo Yanovsky, Ariel Chernomoretz

Examples

```
# Get data tables from an ASpliDU object  
  
du <- aspliDUexample1()  
  
gde <- genesDE( du )  
bdu <- binsDU( du )  
jdu <- junctionsDU( du )  
  
# Set data tables to an ASpliDU object  
  
genesDE( du )     <- gde  
binsDU( du )     <- bdu  
junctionsDU( du ) <- jdu
```

Description

Estimate differential expression at gene level and differential usage at bin level. When targets has only two conditions, and contrast is not set, the estimation of differential expression and usage is done with an exact test, otherwise is estimated using a generalized linear model.

Usage

```
DUreport( counts,
          targets,
          minGenReads = 10,
          minBinReads = 5,
          minRds = 0.05,
          offset = FALSE,
          offsetAggregateMode = c( "geneMode", "binMode" )[1],
          offsetUseFitGeneX = TRUE,
          contrast = NULL,
          forceGLM = FALSE,
          ignoreExternal = TRUE,
          ignoreIo = TRUE,
          ignoreI = FALSE,
          filterWithContrasted = FALSE,
          verbose = FALSE)
```

Arguments

| | |
|----------------|--|
| counts | An object of class ASpliCounts |
| targets | A data.frame containing sample, bam and experimental factor columns. |
| minGenReads | Genes with at least an average of minGenReads reads for any condition are included into the differential expression test. Bins from genes with at least an average of minGenReads reads for all conditions are included into the differential bin usage test. Default value is 10 reads. |
| minBinReads | Bins with at least an average of minGenReads reads for any condition are included into the differential bin usage test. Default value is 5 reads. |
| minRds | Genes with at least an average of minRds read density for any condition are included into the differential expression test. Bins from genes with at least an average of minRds read density for all conditions are included into the differential bin usage test. Bins with at least an average of minRds read density for any condition are included into the differential bin usage test. Default value is 0.05. |
| ignoreExternal | Ignore Exon Bins at the beginning or end of the transcript. Default value is TRUE. |
| ignoreIo | Ignore original introns. Default TRUE |
| ignoreI | Ignore intron bins, test is performed only for exons. Default FALSE |
| offset | Corrects bin expression using an offset matrix derived from gene expression data. Default = FALSE |

| | |
|----------------------|---|
| offsetAggregateMode | Choose the method to aggregate gene counts to create the offset matrix. When offsetAggregateMode is 'geneMode' and option offsetUseFitGeneX is TRUE, a generalized linear model is used to create the offset matrix. When offsetAggregateMode is 'geneMode' and option offsetUseFitGeneX is FALSE, the offset matrix is generated by adding a prior count to the gene count matrix. When offsetAggregateMode is 'binMode' a matrix from obtained from the sum of exonic bin counts, this only takes those bins that passes filters using minGenReads, minBinReads and minRds. Options:=c("geneMode", "binMode")[1] , |
| offsetUseFitGeneX | Default= TRUE |
| contrast | Define the comparison between conditions to be tested. contrast should be a vector with length equal to the number of experimental conditions defined by targets. The values of this vector are the coefficients that will be used to weight each condition, the order of the values corresponds to the order given by getConditions function. When contrast is NULL, defaults to a vector containing -1, as the first value, 1 as the second and zero for all the remaining values, this corresponds to a pair comparison where the first condition is assumed to be a control and the second condition is the treatment, all other conditions are ignored. Default = NULL |
| forceGLM | Force the use of a generalized linear model to estimate differential expression and usage. Default = FALSE |
| filterWithContrasted | A logical value specifying if bins, genes and junction will be filtered by read quantity and read density using data from those conditions that will be used in the comparison, i.e. those which coefficients in contrast argument are different from zero. The default value is FALSE, it is strongly recommended to do not change this value. |
| verbose | A logical value that indicates that detailed information about each step in the analysis will be presented to the user. |

Value

An ASpliDU object with results at genes, bins level.

Author(s)

Estefania Mancini, Javier Iserte, Marcelo Yanovsky, Ariel Chernomoretz

See Also

[edgeR](#), [junctionDUreport](#) Accessors: [genesDE](#), [binsDU](#) Export: [writeDU](#)

Examples

```
# Create a transcript DB from gff/gtf annotation file.
# Warnings in this examples can be ignored.
library(GenomicFeatures)
genomeTxDb <- makeTxDbFromGFF( system.file('extdata', 'genes.mini.gtf',
                                         package="ASpli") )

# Create an ASpliFeatures object from TxDb
features <- binGenome( genomeTxDb )
```

```

# Define bam files, sample names and experimental factors for targets.
bamFileNames <- c( "A_C_0.bam", "A_C_1.bam", "A_C_2.bam",
                  "A_D_0.bam", "A_D_1.bam", "A_D_2.bam" )
targets <- data.frame(
  row.names = paste0('Sample_',c(1:6)),
  bam = system.file( 'extdata', bamFileNames, package="ASpli" ),
  factor1 = c( 'C','C','C','D','D','D' ) )

# Load reads from bam files
bams <- loadBAM( targets )

# Read counts from bam files
counts <- readCounts( features, bams, targets, cores = 1, readLength = 100,
                     maxISize = 50000 )

# Calculate differential usage of genes and bins
du <- DUreport( counts, targets )

# Export results
writeDU( du = du, output.dir = "only_du" )

```

DUreportBinSplice

Differential gene expression and differential bin usage estimation

Description

Estimate differential expression at gene level and differential usage at bin level using diffSpliceDGE function from edgeR package. This is an alternative approach to DUreport. The results at gene level are the same as the results from DUreport. The results at bin level are slightly different.

Usage

```

DUreportBinSplice( counts,
                  targets,
                  minGenReads = 10,
                  minBinReads = 5,
                  minRds = 0.05,
                  contrast = NULL,
                  forceGLM = FALSE,
                  ignoreExternal = TRUE,
                  ignoreIo = TRUE,
                  ignoreI = FALSE,
                  filterWithContrasted = FALSE,
                  verbose = TRUE )

```

Arguments

| | |
|---------|---|
| counts | An object of class ASpliCounts |
| targets | A dataframe containing sample, bam and experimental factor columns. |

| | |
|----------------------|---|
| minGenReads | Genes with at least an average of minGenReads reads for any condition are included into the differential expression test. Bins from genes with at least an average of minGenReads reads for all conditions are included into the differential bin usage test. Default value is 10 reads. |
| minBinReads | Bins with at least an average of minGenReads reads for any condition are included into the differential bin usage test. Default value is 5 reads. |
| minRds | Genes with at least an average of minRds read density for any condition are included into the differential expression test. Bins from genes with at least an average of minRds read density for all conditions are included into the differential bin usage test. Bins with at least an average of minRds read density for any condition are included into the differential bin usage test. Default value is 0.05. |
| ignoreExternal | Ignore Exon Bins at the beginning or end of the transcript. Default value is TRUE. |
| ignoreIo | Ignore original introns. Default TRUE |
| ignoreI | Ignore intron bins, test is performed only for exons. Default FALSE |
| contrast | Define the comparison between conditions to be tested. contrast should be a vector with length equal to the number of experimental conditions defined by targets. The values of this vector are the coefficients that will be used to weight each condition, the order of the values corresponds to the order given by getConditions function. When contrast is NULL, defaults to a vector containing -1, as the first value, 1 as the second and zero for all the remaining values, this corresponds to a pair comparison where the first condition is assumed to be a control and the second condition is the treatment, all other conditions are ignored. Default = NULL |
| forceGLM | Force the use of a generalized linear model to estimate differential expression. It is not used to differential usage of bins. Default = FALSE |
| filterWithContrasted | A logical value specifying if bins, genes and junction will be filtered by read quantity and read density using data from those conditions that will be used in the comparison, i.e. those which coefficients in contrast argument are different from zero. The default value is FALSE, it is strongly recommended to do not change this value. |
| verbose | A logical value that indicates that detailed information about each step in the analysis will be presented to the user. |

Value

An ASpliDU object with results at genes, bins level.

Author(s)

Estefania Mancini, Javier Iserte, Marcelo Yanovsky, Ariel Chernomoretz

See Also

[edgeR](#), [junctionDUreport](#) Accessors: [genesDE](#), [binsDU](#) Export: [writeDU](#)

Examples

```

# Create a transcript DB from gff/gtf annotation file.
# Warnings in this examples can be ignored.
library(GenomicFeatures)
genomeTxDb <- makeTxDbFromGFF( system.file('extdata','genes.mini.gtf',
                                         package="ASpli") )

# Create an ASpliFeatures object from TxDb
features <- binGenome( genomeTxDb )

# Define bam files, sample names and experimental factors for targets.
bamFileNames <- c( "A_C_0.bam", "A_C_1.bam", "A_C_2.bam",
                  "A_D_0.bam", "A_D_1.bam", "A_D_2.bam" )
targets <- data.frame(
  row.names = paste0('Sample_',c(1:6)),
  bam = system.file( 'extdata', bamFileNames, package="ASpli" ),
  factor1 = c( 'C','C','C','D','D','D' ) )

# Load reads from bam files
bams <- loadBAM( targets )

# Read counts from bam files
counts <- readCounts( features, bams, targets, cores = 1, readLength = 100,
                    maxISize = 50000 )

# Calculate differential usage of genes and bins
du <- DUreportBinSplice( counts, targets )

# Export results
writeDU( du = du, output.dir = "only_du" )

```

Examine ASpliDU objects

Examine ASpliDU objects

Description

ASpliDU object may contain results of differential expression of genes, differential usage of bins and junctions, however not everything is calculated at the same or even present. Calculations for genes and bins can be done independently from junctions. Functions `containsJunctions` and `containsGenesAndBins` allow to interrogate an ASpliDU object about the kind of results it contain.

Usage

```

containsJunctions( du )
containsGenesAndBins( du )

```

Arguments

`du` An ASpliDU object.

Value

A logical value that indicates that results for genes and bins, or results for junctions are available in the object.

Author(s)

Estefania Mancini, Marcelo Yanovsky, Ariel Chernomoretz

Examples

```
# Create a transcript DB from gff/gtf annotation file.
# Warnings in this examples can be ignored.
library(GenomicFeatures)
genomeTxDb <- makeTxDbFromGFF( system.file('extdata','genes.mini.gtf',
                                         package="ASpli") )

# Create an ASpliFeatures object from TxDb
features <- binGenome( genomeTxDb )

# Define bam files, sample names and experimental factors for targets.
bamFileNames <- c( "A_C_0.bam", "A_C_1.bam", "A_C_2.bam",
                  "A_D_0.bam", "A_D_1.bam", "A_D_2.bam" )
targets <- data.frame(
  row.names = paste0('Sample_',c(1:6)),
  bam = system.file( 'extdata', bamFileNames, package="ASpli" ),
  factor1 = c( 'C','C','C','D','D','D' ) )

# Load reads from bam files
bams <- loadBAM( targets )

# Read counts from bam files
counts <- readCounts( features, bams, targets, cores = 1, readLength = 100,
                    maxISize = 50000 )

# Create an ASpliDU object.
#
du <- DUreport( counts, targets )

# Verify if du contains results for genes and bins.
containsGenesAndBins( du )
containsJunctions( du )

# Append junction results
du <- junctionDUreport( counts, targets, appendTo = du )

# Verify if du contains results for genes and bins.
containsJunctions( du )
```

Description

ASpli includes functions to easily build ASpli objects, used in examples in the vignette and man pages.

Usage

```
aspliASexample()
aspliBamsExample()
aspliCountsExample()
aspliDUexample1()
aspliDUexample2()
aspliExampleBamList()
aspliExampleGTF()
aspliFeaturesExample()
aspliJunctionDUexample()
aspliTargetsExample()
```

Value

An ASpli object with example data.

Author(s)

Estefania Mancini, Javier Iserte, Marcelo Yanovsky, Ariel Chernomoretz

Examples

```
as <- aspliASexample()
bams <- aspliBamsExample()
counts <- aspliCountsExample()
du1 <- aspliDUexample1()
du2 <- aspliDUexample2()
bamfiles <- aspliExampleBamList()
gtffile <- aspliExampleGTF()
features <- aspliFeaturesExample()
jdu <- aspliJunctionDUexample()
targets <- aspliTargetsExample()
```

Features accesors

Accessors for ASpliFeatures object

Description

Accessors for ASpliFeatures object

Usage

```
featuresg( x )
featuresb( x )
featuresj( x )
```

Arguments

x An ASpliFeatures object

Value

Returns a GenomicRanges object. Function featuresg returns a GRangesList object containing exon ranges for each gene. Functions featuresb and featuresj, returns GRanges object for all bins and junctions.

Author(s)

Estefania Mancini, Javier Iserte, Marcelo Yanovsky, Ariel Chernomoretz

Examples

```
# Get data from an ASpliFeatures object

features <- aspliFeaturesExample()

fg <- featuresg( features )
fb <- featuresb( features )
fj <- featuresj( features )

# Set data to an ASpliFeatures object

featuresg( features ) <- fg
featuresb( features ) <- fb
featuresj( features ) <- fj
```

filterDU

Filtering ASpliDU objects

Description

ASpliDU object can be filtered to retain genes, bins or junction according to their fdr corrected p-value estimated and log-fold-change.

Usage

```
filterDU(
  du ,
  what = c( 'genes', 'bins', 'junctions' ),
  fdr = 1,
  logFC = 0,
  absLogFC = TRUE,
  logFCgreater = TRUE
)
```

Arguments

| | |
|--------------|--|
| du | An ASpliDU object |
| what | A character vector that specifies the kind of features that will be filtered. Accepted values are 'genes', 'bins', 'junctions'. Multiple values can be passed at the same time. The default value is c('genes','bins','junctions') |
| fdr | A double value representing the maximum accepted value of fdr corrected p-value to pass the filter. The default value is 1, the neutral value for fdr filtering operation. |
| logFC | A double value representing the cut-off for accepted values of log-fold-change to pass the filter. The default value is 0, the neutral value for logFC filtering operation if logFCgreater and absLogFC arguments are both TRUE. |
| absLogFC | A logical value that specifies that the absolute value of log-fold-change will be used in the filter operation. The default value is TRUE. |
| logFCgreater | A logical value that specifies that the log-fold-change value (or abs(log-fold-change) if absLogFC argument is TRUE) of features must be greater than the cut-off value to pass the filter. The default value is TRUE. |

Value

A new ASpliDU object with the results of the filtering operations. The elements of features that were not specified to be filtered are kept from the input ASpliDU object.

Author(s)

Estefania Mancini, Javier Iserte, Marcelo Yanovsky, Ariel Chernomoretz

See Also

[DUreport](#), [junctionDUreport](#), [DUreportBinSplice](#),

Examples

```
# Create a transcript DB from gff/gtf annotation file.
# Warnings in this examples can be ignored.
library(GenomicFeatures)
genomeTxDb <- makeTxDbFromGFF( system.file('extdata','genes.mini.gtf',
                                         package="ASpli") )

# Create an ASpliFeatures object from TxDb
features <- binGenome( genomeTxDb )

# Define bam files, sample names and experimental factors for targets.
bamFileNames <- c( "A_C_0.bam", "A_C_1.bam", "A_C_2.bam",
                  "A_D_0.bam", "A_D_1.bam", "A_D_2.bam" )
targets <- data.frame(
  row.names = paste0('Sample_',c(1:6)),
  bam = system.file( 'extdata', bamFileNames, package="ASpli" ),
  factor1 = c( 'C','C','C','D','D','D' ) )

# Load reads from bam files
bams <- loadBAM( targets )
```

```
# Read counts from bam files
counts <- readCounts( features, bams, targets, cores = 1, readLength = 100,
                     maxISize = 50000 )

# Calculate differential usage of junctions only
du <- DUreport( counts, targets )

# Filter by FDR
duFiltered1 <- filterDU( du, what=c('genes','bins'),
                        fdr = 0.01 )

# Filter by logFC, only those that were up-regulated
duFiltered2 <- filterDU( du, what=c('genes','bins'),
                        logFC = log( 1.5, 2 ), absLogFC = FALSE )
```

| | |
|---------------|--|
| getConditions | <i>Retrieve condition names from a targets data frame.</i> |
|---------------|--|

Description

Targets data frame contains experimental factors values for each sample. This function generates a simple name for each unique condition resulting from the combination of all experimental factors. The order of the conditions given by `getConditions` is the same that in contrast argument of `DUreport` function.

Usage

```
getConditions( targets )
```

Arguments

`targets` A dataframe containing sample, bam and experimental factors columns

Value

A character vector with the names of the conditions derived from experimental factors.

Author(s)

Estefania Mancini, Javier Iserte, Marcelo Yanovsky, Ariel Chernomoretz

See Also

[DUreport](#),

Examples

```
# Define bam files, sample names and experimental factors for targets.
bamFileNames <- c( "A_C_0.bam", "A_C_1.bam", "A_C_2.bam",
                  "A_D_0.bam", "A_D_1.bam", "A_D_2.bam" )
targets <- data.frame(
  row.names = paste0('Sample_',c(1:6)),
  bam = system.file( 'extdata', bamFileNames, package="ASpli" ),
  factor1 = c( 'C','C','C','D','D','D' )

# Load reads from bam files.
# Return value is c('C', 'D') in this example.
conditions <- getConditions(targets)

# Define bam files, sample names and experimental factors for targets.
bamFileNames <- c( "A_C_0.bam", "A_C_1.bam", "A_C_2.bam", "A_C_3.bam",
                  "A_D_0.bam", "A_D_1.bam", "A_D_2.bam", "A_D_3.bam" )
targets <- data.frame(
  row.names = paste0('Sample_',c(1:8)),
  bam = file.path( 'extdata', bamFileNames, package="ASpli" ),
  factor1 = c( 'C','C','C','C','D','D','D','D'),
  factor2 = c( 'E','E','F','F','E','E','F','F' )

# Load reads from bam files.
# Return value is c("C_E", "C_F", "D_E", "D_F") in this example.
conditions <- getConditions(targets)
```

junctionDUreport

Differential junction usage estimation

Description

Estimate differential usage at junction level. When targets has only two conditions, and contrast is not set, the estimation of differential expression and usage is done with an exact test, otherwise is estimated using a generalized linear model.

Usage

```
junctionDUreport( counts,
                  targets,
                  appendTo = NULL,
                  minGenReads = 10,
                  minRds = 0.05,
                  threshold = 5,
                  offset = FALSE,
                  offsetUseFitGeneX = TRUE,
                  contrast = NULL,
                  forceGLM = FALSE)
```



```

# Create an ASpliFeatures object from TxDb
features <- binGenome( genomeTxDb )

# Define bam files, sample names and experimental factors for targets.
bamFileNames <- c( "A_C_0.bam", "A_C_1.bam", "A_C_2.bam",
                  "A_D_0.bam", "A_D_1.bam", "A_D_2.bam" )
targets <- data.frame(
  row.names = paste0('Sample_',c(1:6)),
  bam = system.file( 'extdata', bamFileNames, package="ASpli" ),
  factor1 = c( 'C', 'C', 'C', 'D', 'D', 'D' ) )

# Load reads from bam files
bams <- loadBAM( targets )

# Read counts from bam files
counts <- readCounts( features, bams, targets, cores = 1, readLength = 100,
                    maxISize = 50000 )

# Calculate differential usage of junctions only
du <- junctionDUreport( counts, targets )

# Calculate differential usage of genes, bins and junctions
du2 <- DUreport( counts, targets )
du2 <- junctionDUreport( counts, targets, appendTo = du2 )

# Export results
writeDU( du = du, output.dir = "only_du" )

```

loadBAM

Load BAM files

Description

Load BAM files into R session using a targets specification.

Usage

```
loadBAM(targets, cores)
```

Arguments

| | |
|---------|--|
| targets | A data frame containing sample, bam and experimental factors columns |
| cores | Number of processors to use |

Value

A list of GAlignments. Each element of the list correspond to a samples BAM file.

Author(s)

Estefania Mancini, Marcelo Yanovsky, Ariel Chernomoretz

Examples

```
# Define bam files, sample names and experimental factors for targets.
bamFileNames <- c( "A_C_0.bam", "A_C_1.bam", "A_C_2.bam",
                  "A_D_0.bam", "A_D_1.bam", "A_D_2.bam" )

targets <- data.frame(
  row.names = paste0('Sample_',c(1:6)),
  bam = system.file( 'extdata', bamFileNames, package="ASpli" ),
  factor1 = c( 'C','C','C','D','D','D' ) )

# Load reads from bam files
bams <- loadBAM( targets )
```

mergeBinDUAS

*Differential usage of bins and PSI/PIR.***Description**

This function merges the results of differential usage of bins, from an ASpliDU object, with PSI/PIR and junction information, from an ASpliAS object. Also, a delta PSI/PIR value is calculated from a contrast.

Usage

```
mergeBinDUAS( du,
              as,
              targets,
              contrast = NULL )
```

Arguments

| | |
|----------|--|
| du | An object of class ASpliDU |
| as | An object of class ASpliAS |
| targets | A data frame containing sample, bam files and experimental factor columns. |
| contrast | Define the comparison between conditions to be tested. <code>contrast</code> should be a vector with length equal to the number of experimental conditions defined by <code>targets</code> . The values of this vector are the coefficients that will be used to weight each condition, the order of the values corresponds to the order given by <code>getConditions</code> function. When <code>contrast</code> is <code>NULL</code> , defaults to a vector containing -1, as the first value, 1 as the second and zero for all the remaining values, this corresponds to a pair comparison where the first condition is assumed to be a control and the second condition is the treatment, all other conditions are ignored. The default value is <code>NULL</code> . |

Value

A data frame containing feature, event, locus, locus_overlap, symbol, gene coordinates, start of bin, end of bin, bin length, log-Fold-Change value, p-value, fdr corrected p-value, J1 inclusion junction, J1 junction counts for each sample, J2 inclusion junction, J2 junction counts for each sample, J3 exclusion junction, J3 junction counts for each sample, PSI or PIR value for each bin, and delta PSI/PIR.

Author(s)

Estefania Mancini, Javier Iserte, Marcelo Yanovsky, Ariel Chernomoretz

See Also

[ASpliDU](#), [ASpliAS](#)

Examples

```
# Create a transcript DB from gff/gtf annotation file.
# Warnings in this examples can be ignored.
library(GenomicFeatures)
genomeTxDb <- makeTxDbFromGFF( system.file('extdata','genes.mini.gtf',
                                         package="ASpli") )

# Create an ASpliFeatures object from TxDb
features <- binGenome( genomeTxDb )

# Define bam files, sample names and experimental factors for targets.
bamFileNames <- c( "A_C_0.bam", "A_C_1.bam", "A_C_2.bam",
                  "A_D_0.bam", "A_D_1.bam", "A_D_2.bam",
                  "B_C_0.bam", "B_C_1.bam", "B_C_2.bam",
                  "B_D_0.bam", "B_D_1.bam", "B_D_2.bam" )

targets <- data.frame(
  row.names = paste0('Sample_',c(1:12)),
  bam = system.file( 'extdata', bamFileNames, package="ASpli" ),
  factor1 = c( 'A','A','A','A','A','A','B','B','B','B','B','B'),
  factor2 = c( 'C','C','C','D','D','D','C','C','C','D','D','D') )

# Load reads from bam files
bams <- loadBAM( targets )

# Read counts from bam files
counts <- readCounts( features, bams, targets, cores = 1, readLength = 100,
                    maxISize = 50000 )

# Calculate differential usage of genes and bins
du <- DUreport( counts, targets , contrast = c(1,-1,-1,1))

# Calculate PSI / PIR for bins and junction.
as <- AsDiscover( counts, targets, features, bams, readLength = 100,
                threshold = 5, cores = 1 )

mas <- mergeBinDUAS( du, as, targets, contrast = c(1,-1,-1,1) )
```

Description

Creates a plot with gene counts, bin counts, PSI/PIR value, inclusion and exclusion junctions for selected bins and conditions.

Usage

```
plotBins( counts,
          as,
          bin,
          factorsAndValues,
          targets,
          main          = NULL,
          colors        = c( '#2F7955', '#79552F', '#465579',
                             '#A04935', '#752020', '#A07C35' ) ,
          panelTitleColors = '#000000',
          panelTitleCex  = 1,
          innerMargins  = c( 2.1, 3.1, 1.1, 1.1 ),
          outerMargins  = c( 0, 0, 2.4, 0 ),
          useBarplots   = NULL,
          barWidth      = 0.9,
          barSpacer     = 0.4,
          las.x         = 2,
          useHCColors   = FALSE,
          legendAtSide  = TRUE,
          outfolder     = NULL,
          outfileType   = c( 'png', 'bmp', 'jpeg', 'tiff', 'pdf')[1],
          deviceOpt     = NULL )
```

Arguments

| | |
|------------------|---|
| counts | An object of class ASpliCounts |
| as | An object of class ASpliAS |
| bin | A character vector with the names of the bins to be plotted. |
| factorsAndValues | A list containing the factor and the values for each factor to be plotted. The order of the factors will modify how the conditions are grouped in the plot. factorsAndValues must be a named list, where the name of each element is a factor and the list element itself is a character vector of the values of this factor in the order to be plotted. See examples for more details. |
| targets | A data frame containing sample, bam files and experimental factor columns |
| main | Main title of the plot. If NULL the bin name is used as title. |
| colors | A vector of character colors for lines and bar plots. |
| panelTitleColors | A vector of character colors for the titles of each plot panel. |
| panelTitleCex | Character size expansion for panel titles. |
| innerMargins | A numerical vector of the form c(bottom, left, top, right) which gives the size of each plot panel margins. Defaults to c(2.1, 3.1, 1.1, 1.1) |
| outerMargins | A numerical vector of the form c(bottom, left, top, right) which gives the size of margins. Defaults to c(0, 0, 2.4, 0) |

| | |
|--------------|--|
| useBarplots | A logical value that indicates the type of plot to be used. If TRUE bar plots are used, if FALSE lines are used. If NULL the type is bar plot if there just two conditions and lines if there are more than two conditions. |
| barWidth | The width of the bars in bar plots. barWidth must be in (0,1] range. Default value is 0.9. |
| barSpacer | Fraction of barwidth used as spacer between bar plot groups. Default value is 0.4. |
| las.x | Text orientation of x-axis labels. |
| useHCColors | A logical value. If TRUE panelTitleColors are not used, instead panel title are automatically chosen to have high contrast against colors. |
| legendAtSide | A logical value that forces panel title to be shown on the y-axis, instead of over the plot. |
| outfolder | Path to output folder to write plot images. Is NULL, plot are rendered on the default device |
| outfileType | File format of the output files used if outfolder is not NULL. Accepted values are 'png', 'jpeg', 'tiff', 'pdf'. Each value selects the graphic device of the same name. The name of the image file is the name of bin with the corresponding extension given by the chosen type |
| deviceOpt | A list of named options to be passed to the graphic device selected in outfileType |

Author(s)

Estefania Mancini, Javier Iserte, Marcelo Yanovsky, Ariel Chernomoretz

See Also

[plotGenomicRegions](#),

Examples

```
# Create a transcript DB from gff/gtf annotation file.
# Warnings in this examples can be ignored.
library(GenomicFeatures)
genomeTxDb <- makeTxDbFromGFF( system.file('extdata','genes.mini.gtf',
                                         package="ASpli") )

# Create an ASpliFeatures object from TxDb
features <- binGenome( genomeTxDb )

# Define bam files, sample names and experimental factors for targets.
bamFileNames <- c( "A_C_0.bam", "A_C_1.bam", "A_C_2.bam",
                  "A_D_0.bam", "A_D_1.bam", "A_D_2.bam",
                  "B_C_0.bam", "B_C_1.bam", "B_C_2.bam",
                  "B_D_0.bam", "B_D_1.bam", "B_D_2.bam" )

targets <- data.frame(
  row.names = paste0('Sample_',c(1:12)),
  bam = system.file( 'extdata', bamFileNames, package="ASpli" ),
  factor1 = c( 'A', 'A', 'A', 'A', 'A', 'A', 'B', 'B', 'B', 'B', 'B', 'B' ),
  factor2 = c( 'C', 'C', 'C', 'D', 'D', 'D', 'C', 'C', 'C', 'D', 'D', 'D' ) )

# Load reads from bam files
```

```

bams <- loadBAM( targets )

# Read counts from bam files
counts <- readCounts( features, bams, targets, cores = 1, readLength = 100,
                      maxISize = 50000 )

# Calculate differential usage of genes, bins and junctions
du <- DUreport( counts, targets , contrast = c(1,-1,-1,1))
du <- junctionDUreport( counts, targets, appendTo = du, contrast = c(1,-1,-1,1))

# Calculate PSI / PIR for bins and junction.
as <- AsDiscover( counts, targets, features, bams, readLength = 100,
                  threshold = 5, cores = 1 )

# Plot bin data. Factor2 is the main factor for graphic representation in
# this example as it is the first in factorsAndValues argument.
# This makes a bar plot comparing four conditions, grouped by factor1.
plotBins( counts, as, 'GENE03:E002',
          factorsAndValues = list(
            factor2 = c('C','D'),
            factor1 = c('A','B') ),
          las.x = 1,
          legendAtSide = TRUE,
          useHCColors = TRUE,
          targets = targets,
          barWidth = 0.95,
          innerMargins = c( 2.1, 4.1, 1.1, 1.1 ) )

# Redefine targets
targets <- data.frame(
  row.names = paste0('Sample_',c(1:12)),
  bam = system.file( 'extdata', bamFileNames, package="ASpli" ),
  factor1 = c( 'A','A','B','B','C','C','D','D','E','E','F','F' ) )

as <- AsDiscover( counts, targets, features, bams, readLength = 100,
                  threshold = 5, cores = 1 )

# This makes a line plot for six conditions, grouped by factor1.
plotBins( counts, as, 'GENE03:E002',
          factorsAndValues = list(
            factor1 = c('A','B','C','D','E','F') ),
          las.x = 1,
          legendAtSide = FALSE,
          targets = targets,
          innerMargins = c( 2.1, 4.1, 1.1, 1.1 ) )

```

plotGenomicRegions *Create genomic regions coverage plots*

Description

Graphic representation of coverage and junctions is useful to complement the results of differential usage of bins and junction and differential expression analysis.

Function `plotGenomicRegions` allow to create plots for multiple conditions for bins and genes. Each individual plot can only correspond to a single gene or bin, but can contain many panels for different experimental conditions.

Usage

```
plotGenomicRegions( features, x, genomeTxD, targets, xIsBin = TRUE,
  layout = 'auto', colors = 'auto', plotTitles = 'auto', sashimi = FALSE,
  zoomOnBins = FALSE, deviceOpt = NULL, highLightBin = TRUE, outfolder = NULL,
  outfileType = 'png', mainFontSize = 24, annotationHeight = 0.2,
  annotationCol = 'black', annotationFill = 'gray', annotationColTitle = 'black',
  preMergedBAMs = NULL, useTransparency = FALSE, tempFolder = 'tmp',
  avoidReMergeBams = FALSE, verbose = TRUE )
```

Arguments

| | |
|---------------------------|--|
| <code>features</code> | An <code>ASpliFeatures</code> object, generated with <code>binGenoms</code> function. |
| <code>x</code> | A character vector with the names of bins or genes to plot. To plot into a window is recommended that the length of <code>x</code> be one. |
| <code>genomeTxD</code> | A <code>TxD</code> object with the annotation of reference genome. |
| <code>targets</code> | A data frame containing sample, bam files and experimental factor columns |
| <code>xIsBin</code> | A logical value that indicates if values in <code>x</code> corresponds to gene names or bin names. |
| <code>layout</code> | A character with value 'auto' or a character matrix with condition names arranged with the desired layout of the panels in plots. The dimensions of layout matrix, colors matrix and plotTitles matrices must be the same. Matrix can have NA values, however, the height of the panels corresponding to that column are modified to occupy the total height. The default value is 'auto'. |
| <code>colors</code> | A character containing value 'auto' or containing colors strings, or a character matrix with color names arranged with the layout specified in layout argument. The dimensions of layout matrix, colors matrix and plotTitles matrices must be the same. The default value is 'auto'. |
| <code>plotTitles</code> | A character containing value 'auto', or a character matrix with titles for each panel arranged with the layout specified in layout argument. The dimensions of layout matrix, colors matrix and plotTitles matrices must be the same. The default value is 'auto'. |
| <code>sashimi</code> | A logical value that specifies that a sashimi plot for junctions must be included into each panel. The default value is FALSE. |
| <code>zoomOnBins</code> | A FALSE logical value or a double value between 0 and 1. If value is FALSE then the genomic range to be plotted correspond to the complete gene, otherwise the genomic range is that the size of the bin corresponds to a fraction equals to zoomOnBins value of the total and is centered in the bin. Is used only when <code>xIsBin</code> is TRUE. The default value is FALSE. |
| <code>deviceOpt</code> | A named list of arguments to be passed to the graphic device used to plot. This allow to further customization of the plot. The default value is an empty list. |
| <code>highLightBin</code> | A logical value that indicates if the bin should be highlighted. The default value is TRUE. |
| <code>outfolder</code> | NULL or a character vector representing a folder path that will be used to save the plot images. If the folder doesn't exists it is created. If NULL, the plot is |

made in a window. The default value is NULL. For each bin, a single image file is generated. The name of the file is the name of the bin, added with a '.gr.' string, and the file extension at the end. If the name of the bin contains invalid character for a file name, those will be replaced by an underscore character.

| | |
|--------------------|--|
| outfileType | A character value the specifies the file format of the plot to be created. Is used only when outfolder is not NULL. Accepted values are 'png', 'jpeg', 'bmp', 'tiff', 'pdf'. Each value is the graphic device used to create the image. The default value is 'png'. |
| mainFontSize | A numeric value specifying the size of the main title. The default value is 24. |
| annotationHeight | A double value specifying the proportion of the total height used to represent the gene model. The default value is 0.2. |
| annotationCol | A character value that specifies the color of the borders of bars in gene model representation. The default value is 'black'. |
| annotationFill | A character value that specifies the color of the filling of bars in gene model representation. The default value is 'gray'. |
| annotationColTitle | A character value that specifies the color of text in gene model representation. The default value is 'black'. |
| preMergedBAMs | A one column data frame that associates a condition, specified in the row name, with a character value representing the path of bam file with the reads for that condition. This bam file is typically generated by merging the bam files of all replicates for that condition. The default value is NULL, this specifies that not merged bam files are used, instead on-the-fly read extraction and merging is done from the bam files specified in the targets argument. |
| useTransparency | A logical value that specifies if transparency will be used to generate the plots, this leads to better looking plot, however not all graphic devices support transparency. The default value is FALSE. |
| tempFolder | A character value specifying the path to store intermediate files produced while extracting and merging reads from bam files. It is only used when preMerged-BAMs arguments is NULL. The files created are not automatically removed after plotting because can be reused to create a new plot of the same genes or bins with different graphic options. The default value is 'tmp', that means a new 'tmp' folder in the current working folder. |
| avoidReMergeBams | A logical value specifying that extraction and merging of bam files will be avoided. This is only meaningful when the extraction and merging of the same set of genes and bins was done in the previous execution of plotGenomicRegions function. The default value is FALSE. |
| verbose | A logical value specifying that detailed information about the execution will be informed to the user. The default value is TRUE. |

Author(s)

Estefania Mancini, Javier Iserte, Marcelo Yanovsky, Ariel Chernomoretz

See Also

[Devices](#), [pdf](#), [png](#), [bmp](#), [jpeg](#), [tiff](#)

Examples

```

# Create a transcript DB from gff/gtf annotation file.
# Warnings in this examples can be ignored.
library(GenomicFeatures)
genomeTxDb <- makeTxDbFromGFF( system.file('extdata','genes.mini.gtf',
                                         package="ASpli") )

# Create an ASpliFeatures object from TxDb
features <- binGenome( genomeTxDb )

# Define bam files, sample names and experimental factors for targets.
bamFileNames <- c( "A_C_0.bam", "A_C_1.bam", "A_C_2.bam",
                  "A_D_0.bam", "A_D_1.bam", "A_D_2.bam" )
targets <- data.frame(
  row.names = paste0('Sample_',c(1:6)),
  bam = system.file( 'extdata', bamFileNames, package="ASpli" ),
  factor1 = c( 'C','C','C','D','D','D'),
  stringsAsFactors = FALSE )

# Plot a single bin to a window
plotGenomicRegions(
  features,
  'GENE01:E002',
  genomeTxDb,
  targets,
  sashimi = FALSE,
  colors = '#AA4444',
  annotationHeight = 0.1,
  tempFolder = 'tmp',
  verbose = TRUE ,
  avoidReMergeBams = FALSE,
  useTransparency = FALSE )

# plot two bins to pdf files.
plotGenomicRegions(
  features, c( 'GENE01:E002', 'GENE02:E002' ),
  genomeTxDb,
  targets,
  layout = matrix( c( 'C', 'D'), ncol = 1),
  colors = matrix( c( '#663243', '#363273'), ncol = 1),
  plotTitles = matrix( c( 'C condition', 'D condition'), ncol = 1),
  sashimi = FALSE,
  mainFontSize = 12,
  annotationHeight = 0.1,
  tempFolder = 'tmp',
  verbose = TRUE ,
  avoidReMergeBams = FALSE,
  useTransparency = TRUE,
  outfolder = '.',
  outfileType = 'pdf',
  deviceOpt = list( height = 6, width = 5, paper = 'a4r' ) )

```

Description

Read density of gene and bins is the quotient between the number of read counts and the length of the feature. The results are appended into an ASpliCounts object that must be given as argument. The explicit calculation of read densities is usually not required because is automatically performed by readCounts function.

Usage

```
rds( counts, targets )
```

Arguments

| | |
|---------|--|
| counts | An ASpliCounts object |
| targets | A data frame containing sample, bam and experimental factors columns |

Value

An ASpliCounts object containing read densities of genes and bins.

Author(s)

Estefania Mancini, Javier Iserte, Marcelo Yanovsky, Ariel Chernomoretz

Examples

```
# Create a transcript DB from gff/gtf annotation file.
# Warnings in this examples can be ignored.
library(GenomicFeatures)
genomeTxDb <- makeTxDbFromGFF( system.file('extdata','genes.mini.gtf',
                                         package="ASpli") )

# Create an ASpliFeatures object from TxDb
features <- binGenome( genomeTxDb )

# Define bam files, sample names and experimental factors for targets.
bamFileNames <- c( "A_C_0.bam", "A_C_1.bam", "A_C_2.bam",
                  "A_D_0.bam", "A_D_1.bam", "A_D_2.bam" )
targets <- data.frame(
  row.names = paste0('Sample_',c(1:6)),
  bam = system.file( 'extdata', bamFileNames, package="ASpli" ),
  factor1 = c( 'C','C','C','D','D','D' ) )

# Load reads from bam files
bams <- loadBAM( targets )

# Read counts from bam files
counts <- readCounts( features, bams, targets, cores = 1, readLength = 100,
                    maxISize = 50000 )

# Calculates read densities
counts <- rds( counts, targets )
```

| | |
|------------|--------------------------------|
| readCounts | <i>Summarize read overlaps</i> |
|------------|--------------------------------|

Description

Summarize read overlaps against all feature levels

Usage

```
readCounts( features, bam, targets, cores = 1, readLength,
            maxISize, minAnchor = 10)
```

Arguments

| | |
|------------|---|
| features | An object of class ASpliFeatures. It is a list of GRanges at gene, bin and junction level |
| bam | List of GAlignments objects corresponding to bam files of samples. |
| targets | A dataframe containing sample, bam and experimental factors columns |
| readLength | Read length of sequenced library. It is used for compute E1I and IE2 read summarization |
| maxISize | maximum intron expected size. Junctions longer than this size will be discarded |
| cores | Number of cores to use. Default is 1 |
| minAnchor | Minimum percentage of read that should be aligned to an exon-intron boundary |

Value

An object of class ASpliCounts. Each slot is a dataframe containing features metadata and read counts. Summarization is reported at gene, bin, junction and intron flanking regions (E1I, IE2).

Author(s)

Estefania Mancini, Javier Iserte, Marcelo Yanovsky, Ariel Chernomoretz

See Also

Accessors: [countsg](#), [countsb](#), [countsj](#), [countseli](#), [countsie2](#), [rdsg](#), [rdsb](#), Export: [writeCounts](#)

Examples

```
# Create a transcript DB from gff/gtf annotation file.
# Warnings in this examples can be ignored.
library(GenomicFeatures)
genomeTxDb <- makeTxDbFromGFF( system.file('extdata','genes.mini.gtf',
                                         package="ASpli") )

# Create an ASpliFeatures object from TxDb
features <- binGenome( genomeTxDb )

# Define bam files, sample names and experimental factors for targets.
bamFileNames <- c( "A_C_0.bam", "A_C_1.bam", "A_C_2.bam",
                  "A_D_0.bam", "A_D_1.bam", "A_D_2.bam" )
```

```
targets <- data.frame(
  row.names = paste0('Sample_',c(1:6)),
  bam = system.file( 'extdata', bamFileNames, package="ASpli" ),
  factor1 = c( 'C','C','C','D','D','D' ) )

# Load reads from bam files
bams <- loadBAM( targets )

# Read counts from bam files
counts <- readCounts( features, bams, targets, cores = 1, readLength = 100,
  maxISize = 50000 )

# Export data
writeCounts( counts, output.dir = "only_counts" )
```

show-methods

Display a summary of data contained in ASpliObjects

Description

Display a summary of data contained in ASpliObjects

Details

Display a summary of data contained in ASpliObjects

Author(s)

Estefania Mancini, Javier Iserte, Marcelo Yanovsky, Ariel Chernomoretz

Subset ASpli objects

Subset ASpli objects

Description

ASpli provides utility functions to easy subset ASpliCounts objects, ASpliAS objects, targets data frame and lists GAlignments generated with loadBAM function. The subset can be done selecting some of the experimental conditions or samples names (but not both).

Usage

```
subset( x, ... )
subsetBams( x, targets, select )
subsetTargets( targets, select, removeRedundantExpFactors )
```

Arguments

| | |
|---------------------------|---|
| x | An ASpliCount or ASpliAS object for subset function, or list of GAlignments for subsetBams function. |
| targets | A dataframe containing sample, bam and experimental factor columns. |
| select | A character vector specifying the conditions or samples to be kept after subset operation. It's assumed that condition names are different from sample names. |
| removeRedundantExpFactors | When sub-setting the targets data frame, one or more experimental factors can have only one value. If this argument is TRUE those experimental factors are absent in the resulting target data frame. |
| ... | Subsetting ASpliCounts and ASpliAS objects sub subset method requires a targets argument and a select argument with the same specifications that the arguments with the same name in subsetBams and subsetTargets functions |

Value

A data frame similar to x (or targets for subsetTargets) with only the containing only the selected elements.

Author(s)

Estefania Mancini, Marcelo Yanovsky, Ariel Chernomoretz

Examples

```
# Create a transcript DB from gff/gtf annotation file.
# Warnings in this examples can be ignored.
library(GenomicFeatures)
genomeTxDb <- makeTxDbFromGFF( system.file('extdata','genes.mini.gtf',
                                         package="ASpli") )

# Create an ASpliFeatures object from TxDb
features <- binGenome( genomeTxDb )

# Define bam files, sample names and experimental factors for targets.
bamFileNames <- c( "A_C_0.bam", "A_C_1.bam", "A_C_2.bam",
                  "A_D_0.bam", "A_D_1.bam", "A_D_2.bam" )
targets <- data.frame(
  row.names = paste0('Sample_',c(1:6)),
  bam = system.file( 'extdata', bamFileNames, package="ASpli" ),
  factor1 = c( 'C','C','C','D','D','D' ) )

# Load reads from bam files
bams <- loadBAM( targets )

# Read counts from bam files
counts <- readCounts( features, bams, targets, cores = 1, readLength = 100,
                    maxISize = 50000 )

# Create ASpliAS object
as <- AsDiscover( counts, targets, features, bams, readLength = 100,
                threshold = 5, cores = 1 )
```

```
# Define selection
select <- c('Sample_1', 'Sample_2', 'Sample_4', 'Sample_5')

# Subset target
targets2 <- subsetTargets( targets, select )

# Subset bams
bams2 <- subsetBams( bams, targets, select )

# Subset ASpliCounts object
counts2 <- subset( counts, targets, select )

# Subset ASpliAS object
as2 <- subset( as, targets, select )
```

write

Write results

Description

Export tab delimited files in structured output

Usage

```
writeCounts(counts, output.dir="counts")
writeRds(counts, output.dir="rds")
writeDU(du, output.dir="du")
writeAS(as, output.dir="as")
writeAll(counts, du, as, output.dir="output")
```

Arguments

| | |
|------------|---|
| counts | An ASpliCounts object |
| as | An ASpliAS object |
| du | An ASpliDU object |
| output.dir | Name of output folder (new or existing) |

Value

Tab delimited files are exported in a tidy manner into output folder

Author(s)

Estefania Mancini, Javier Iserte, Marcelo Yanovsky, Ariel Chernomoretz

See Also

[AsDiscover](#), [binGenome](#), [DUreport](#)

write-methods

Write results

Description

Export tab delimited files in structured output

Details

Tab delimited files are exported in a tidy manner into output folder

Author(s)

Estefania Mancini, Javier Iserte, Marcelo Yanovsky, Ariel Chernomoretz

See Also

[AsDiscover](#), [binGenome](#), [DUreport](#)

Index

*Topic **alternative splicing, RNA-seq, junctions**

- ASpli-package, 2
- altPSI, 6, 7
- altPSI (AS accessors), 4
- altPSI, ASpliAS-method (ASpliAS-class), 6
- altPSI<- (AS accessors), 4
- altPSI<-, ASpliAS, data.frame-method (ASpliAS-class), 6
- AS accessors, 4
- ASDiscover, 5, 7, 39, 40
- ASDiscover, ASpliCounts-method (ASpliCounts-class), 8
- ASpli (ASpli-package), 2
- ASpli-package, 2
- ASpliAS, 28
- ASpliAS (ASpliAS-class), 6
- ASpliAS-class, 6
- aspliASexample (Example data), 19
- aspliBamsExample (Example data), 19
- ASpliCounts, 7
- ASpliCounts-class, 8
- aspliCountsExample (Example data), 19
- ASpliDU, 28
- ASpliDU (ASpliDU-class), 9
- ASpliDU-class, 9
- aspliDUexample1 (Example data), 19
- aspliDUexample2 (Example data), 19
- aspliExampleBamList (Example data), 19
- aspliExampleGTF (Example data), 19
- ASpliFeatures-class, 9
- aspliFeaturesExample (Example data), 19
- aspliJunctionDUexample (Example data), 19
- aspliTargetsExample (Example data), 19

- binGenome, 10, 39, 40
- binGenome, TxDb-method (binGenome-methods), 11
- binGenome-methods, 11
- binsDU, 15, 17
- binsDU (DU accessors), 13
- binsDU, ASpliDU-method (ASpliDU-class), 9

- binsDU<- (DU accessors), 13
- binsDU<-, ASpliDU-method (ASpliDU-class), 9
- bmp, 33

- containsGenesAndBins (Examine ASpliDU objects), 18
- containsGenesAndBins, ASpliDU-method (ASpliDU-class), 9
- containsJunctions (Examine ASpliDU objects), 18
- containsJunctions, ASpliDU-method (ASpliDU-class), 9
- Counts accesors, 12
- countsb, 36
- countsb (Counts accesors), 12
- countsb, ASpliCounts-method (ASpliCounts-class), 8
- countsb<- (Counts accesors), 12
- countsb<-, ASpliCounts, data.frame-method (ASpliCounts-class), 8
- countse1i, 36
- countse1i (Counts accesors), 12
- countse1i, ASpliCounts-method (ASpliCounts-class), 8
- countse1i<- (Counts accesors), 12
- countse1i<-, ASpliCounts, data.frame-method (ASpliCounts-class), 8
- countsg, 36
- countsg (Counts accesors), 12
- countsg, ASpliCounts-method (ASpliCounts-class), 8
- countsg<- (Counts accesors), 12
- countsg<-, ASpliCounts, data.frame-method (ASpliCounts-class), 8
- countsie2, 36
- countsie2 (Counts accesors), 12
- countsie2, ASpliCounts-method (ASpliCounts-class), 8
- countsie2<- (Counts accesors), 12
- countsie2<-, ASpliCounts, data.frame-method (ASpliCounts-class), 8
- countsj, 36
- countsj (Counts accesors), 12

- countsj, ASpliCounts-method
(ASpliCounts-class), 8
- countsj<- (Counts accesors), 12
- countsj<- ,ASpliCounts, data.frame-method
(ASpliCounts-class), 8

- Devices, 33
- DU accesors, 13
- DUreport, 14, 22, 23, 25, 39, 40
- DUreport, ASpliCounts-method
(ASpliCounts-class), 8
- DUreportBinSplice, 16, 22
- DUreportBinSplice, ASpliCounts-method
(ASpliCounts-class), 8

- edgeR, 15, 17, 25
- esPSI, 6, 7
- esPSI (AS accesors), 4
- esPSI, ASpliAS-method (ASpliAS-class), 6
- esPSI<- (AS accesors), 4
- esPSI<- ,ASpliAS, data.frame-method
(ASpliAS-class), 6
- Examine ASpliDU objects, 18
- Example data, 19

- Features accesors, 20
- featuresb, 11
- featuresb (Features accesors), 20
- featuresb, ASpliFeatures-method
(ASpliFeatures-class), 9
- featuresb<- (Features accesors), 20
- featuresb<- ,ASpliFeatures, GRanges-method
(ASpliFeatures-class), 9
- featuresg, 11
- featuresg (Features accesors), 20
- featuresg, ASpliFeatures-method
(ASpliFeatures-class), 9
- featuresg<- (Features accesors), 20
- featuresg<- ,ASpliFeatures, GRangesList-method
(ASpliFeatures-class), 9
- featuresj, 11
- featuresj (Features accesors), 20
- featuresj, ASpliFeatures-method
(ASpliFeatures-class), 9
- featuresj<- (Features accesors), 20
- featuresj<- ,ASpliFeatures, GRanges-method
(ASpliFeatures-class), 9
- filterDU, 21
- filterDU, ASpliDU-method
(ASpliDU-class), 9

- genesDE, 15, 17
- genesDE (DU accesors), 13

- genesDE, ASpliDU-method (ASpliDU-class),
9
- genesDE<- (DU accesors), 13
- genesDE<- ,ASpliDU, data.frame-method
(ASpliDU-class), 9
- getConditions, 23

- irPIR, 6, 7
- irPIR (AS accesors), 4
- irPIR, ASpliAS-method (ASpliAS-class), 6
- irPIR<- (AS accesors), 4
- irPIR<- ,ASpliAS, data.frame-method
(ASpliAS-class), 6

- joint, 7
- joint (AS accesors), 4
- joint, ASpliAS-method (ASpliAS-class), 6
- joint<- (AS accesors), 4
- joint<- ,ASpliAS, data.frame-method
(ASpliAS-class), 6
- jpeg, 33
- junctionDUreport, 15, 17, 22, 24
- junctionDUreport, ASpliCounts-method
(ASpliCounts-class), 8
- junctionsDU, 25
- junctionsDU (DU accesors), 13
- junctionsDU, ASpliDU-method
(ASpliDU-class), 9
- junctionsDU<- (DU accesors), 13
- junctionsDU<- ,ASpliDU, data.frame-method
(ASpliDU-class), 9
- junctionsPIR, 6, 7
- junctionsPIR (AS accesors), 4
- junctionsPIR, ASpliAS-method
(ASpliAS-class), 6
- junctionsPIR<- (AS accesors), 4
- junctionsPIR<- ,ASpliAS, data.frame-method
(ASpliAS-class), 6
- junctionsPSI, 6, 7
- junctionsPSI (AS accesors), 4
- junctionsPSI, ASpliAS-method
(ASpliAS-class), 6
- junctionsPSI<- (AS accesors), 4
- junctionsPSI<- ,ASpliAS, data.frame-method
(ASpliAS-class), 6

- loadBAM, 26

- mergeBinDUAS, 27
- mergeBinDUAS, ASpliDU, ASpliAS-method
(ASpliDU-class), 9

- pdf, 33

- plotBins, 28
- plotBins, ASpliCounts-method
(ASpliCounts-class), 8
- plotGenomicRegions, 30, 31
- plotGenomicRegions, ASpliFeatures-method
(ASpliFeatures-class), 9
- png, 33
- rds, 34
- rds, ASpliCounts-method
(ASpliCounts-class), 8
- rdsb, 36
- rdsb (Counts accesors), 12
- rdsb, ASpliCounts-method
(ASpliCounts-class), 8
- rdsb<- (Counts accesors), 12
- rdsb<-, ASpliCounts, data.frame-method
(ASpliCounts-class), 8
- rdsg, 36
- rdsg (Counts accesors), 12
- rdsg, ASpliCounts-method
(ASpliCounts-class), 8
- rdsg<- (Counts accesors), 12
- rdsg<-, ASpliCounts, data.frame-method
(ASpliCounts-class), 8
- readCounts, 36
- readCounts, ASpliFeatures-method
(ASpliFeatures-class), 9
- show, ASpliAS-method (show-methods), 37
- show, ASpliCounts-method (show-methods),
37
- show, ASpliDU-method (show-methods), 37
- show, ASpliFeatures-method
(show-methods), 37
- show-methods, 37
- subset (Subset ASpli objects), 37
- Subset ASpli objects, 37
- subset, ASpliAS-method (ASpliAS-class), 6
- subset, ASpliCounts-method
(ASpliCounts-class), 8
- subsetBams (Subset ASpli objects), 37
- subsetTargets (Subset ASpli objects), 37
- tiff, 33
- write, 39
- write-methods, 40
- writeAll (write), 39
- writeAll, ANY-method (write-methods), 40
- writeAll, ASpliCounts-method
(ASpliCounts-class), 8
- writeAS, 6
- writeAS (write), 39
- writeAS, ASpliAS-method (ASpliAS-class),
6
- writeAS-methods (write-methods), 40
- writeCounts, 36
- writeCounts (write), 39
- writeCounts, ASpliCounts-method
(ASpliCounts-class), 8
- writeCounts-methods (write-methods), 40
- writeDU, 15, 17, 25
- writeDU (write), 39
- writeDU, ASpliDU-method (ASpliDU-class),
9
- writeDU-methods (write-methods), 40
- writeRds (write), 39
- writeRds, ASpliCounts-method
(ASpliCounts-class), 8
- writeRds-methods (write-methods), 40