

RWebServices

April 20, 2011

ArrayAndMatrix-class

Class "NumericMatrix" and friends

Description

Classes providing `matrix` and `array` functionality, but allowing stronger type specification, e.g., `NumericMatrix` is a `matrix` whose members must be of type "numeric". A "matrix" is two-dimensional; an "array" is any dimensions, but R treats two-dimensional arrays as "matrix" and one-dimensional arrays as "vector" so "XxxArray" is most useful for specifying arrays with greater than 2 dimensions.

Available classes are "RawMatrix" "CharMatrix" "LogicalMatrix" "IntegerMatrix" "NumericMatrix" "ComplexMatrix" "RawArray" "CharArray" "LogicalArray" "IntegerArray" "NumericArray" "ComplexArray".

Details

The following illustrates how to use these classes in R and Java, using `NumericMatrix` as an example.

The examples assume that mapping between R and Java uses the "javalib" type mode.

Suppose you would like an R function to return a matrix of numeric (double) values, and that you are using the "javalib" mode for mapping between R and Java (`typeMode="javalib"` in `createMap`, or `typemode=javalib` in the ant configuration file `RWebServicesTuning.properties`). For this type mode, specifying "matrix" as a return type is insufficient: a matrix could contain any basic type (raw, character, integer, double, complex, etc.), so there is not enough information to map to a Java object. The solution is to specify more clearly what the type of the return value is, for instance, if the return type is a matrix of numeric (double) values, then arrange for the function to return an object of class `NumericMatrix`.

In R the basic properties of `NumericMatrix` can be seen here:

```
> nm=new("NumericMatrix", matrix(as.double(50:1),10,5))
> dim(nm)
[1] 10  5
> nm[7,3]
[1] 24
> as.vector(nm)
[1] 50 49 48 47 46 45 44 43 42 41 40 39 38 37 36 35 34 33
```

```
[19] 32 31 30 29 28 27 26 25 24 23 22 21 20 19 18 17 16 15
[37] 14 13 12 11 10 9 8 7 6 5 4 3 2 1
> as.vector(nm)[(3-1)*nrow(nm)+7]
[1] 24
```

The last line is meant to illustrate that the 'matrix' data in R is stored as a single vector, in 'column-major' order, i.e., elements $1:nrow(nm)$ are the first column, $(nrow(nm)+1):(2*nrow(nm))$ are the second column, etc.

In Java, `dim=getDim()` returns an `int[]`, containing the number of rows and the number of columns, e.g., `int[] = {10, 5}` for the example above of columns in the matrix (like `dim()` would do on a matrix in R).

`value=getValue()` will return `double[]`, containing all the data, like the result of `as.vector` above. Remembering that Java starts indexing at 0, we can get the element in row `i` and column `j` as

```
value[i * dim[0] + j]
```

We (or you) could write methods `getMatrix` / `setMatrix` returning / taking `double[][]` to do this, or `getElement` / `setElement` to access specific elements; it's worthwhile remembering that this does require quite a bit of memory allocation (for big arrays), so in some ways it's better to force the client to just give the data in the expected format anyway.

Objects from the Class

Objects can be created by calls of the form `new("NumericMatrix", ...)`. To create an instance from an existing, untyped, "matrix" or "array", use forms like `new("NumericMatrix", m)` or `unclass` and update the mode of the object. See examples for additional detail.

Slots

None.

Extends

Class "matrix", from data part. Class "structure", by class "matrix", distance 2. Class "array", by class "matrix", distance 2. Class "vector", by class "matrix", distance 3, with explicit coerce. Class "vector", by class "matrix", distance 4, with explicit coerce.

Methods

Use "NumericMatrix" and friends as replacements for "matrix" or "array".

Author(s)

Martin Morgan <mtmorgan@fhcrc.org>

Examples

```
## creating an empty instance
obj <- new("ComplexMatrix")
obj
mode(obj)
## Converting between array and typed Array
new("RawArray", array(raw(), dim=c(5,2,3)))
```

```
## Converting between types
obj <- new("NumericMatrix", matrix(numeric()))
obj <- unclass(obj) # retrieve underlying matrix
mode(obj) <- "raw"
obj <- new("RawMatrix", obj)
validObject(obj)
obj
```

converters

Convert between R objects and their Java representation.

Description

These functions are not intended for the end user. They are used to match objects being translated between R and Java to functions that perform the conversion. They are useful for understanding the overall conversion process, and as examples for writing custom conversions.

Usage

```
# 'robject' converters
cvtCharacterFromJava(x, thisClassName)
cvtCharacterToJava(x, ...)
matchCharacterToJava(x, ...)

cvtIntegerFromJava(x, thisClassName)
cvtIntegerToJava(x, ...)
matchIntegerToJava(x, ...)

cvtLogicalFromJava(x, thisClassName)
cvtLogicalToJava(x, ...)
matchLogicalToJava(x, ...)

cvtNumericFromJava(x, thisClassName)
cvtNumericToJava(x, ...)
matchNumericToJava(x, ...)

cvtRawFromJava(x, thisClassName)
cvtRawToJava(x, ...)
matchRawToJava(x, ...)

cvtComplexFromJava(x, thisClassName)
cvtComplexToJava(x, ...)
matchComplexToJava(x, ...)

cvtVectorFromJava(x, thisClassName)
cvtVectorToJava(x, ...)
matchVectorToJava(x, ...)

cvtListFromJava(x, thisClassName)
cvtListToJava(x, ...)
matchListToJava(x, ...)
```

```
cvtArrayFromJava(x, thisClassName)
cvtArrayToJava(x, ...)
matchArrayToJava(x, ...)

cvtMatrixFromJava(x, thisClassName)
cvtMatrixToJava(x, ...)
matchMatrixToJava(x, ...)

cvtFactorFromJava(x, thisClassName)
cvtFactorToJava(x, ...)
matchFactorToJava(x, ...)

cvtDataFrameFromJava(x, thisClassName)
cvtDataFrameToJava(x, ...)
matchDataFrameToJava(x, ...)

cvtEnvFromJava(x, thisClassName)
cvtEnvToJava(x, ...)
matchEnvToJava(x, ...)

cvtUnknownFromJava(x, thisClassName)
cvtUnknownToJava(x, ...)
matchUnknownToJava(x, ...)

cvtFileReferencesFromJava(x, thisClassName)
cvtFileReferencesToJava(x, ...)
matchFileReferencesToJava(x, ...)

## 'javalib' converters
cvtCharacterToJava2(x, ...)
matchCharacterToJava2(x, ...)

cvtIntegerToJava2(x, ...)
matchIntegerToJava2(x, ...)

cvtLogicalToJava2(x, ...)
matchLogicalToJava2(x, ...)

cvtNumericToJava2(x, ...)
matchNumericToJava2(x, ...)

cvtRawToJava2(x, ...)
matchRawToJava2(x, ...)

cvtComplexFromJava2(x, thisClassName)
cvtComplexToJava2(x, ...)
matchComplexToJava2(x, ...)

cvtListToJava2(x, ...)
matchListToJava2(x, ...)
```

```
cvtFactorFromJava2(x, thisClassName)
cvtFactorToJava2(x, ...)
matchFactorToJava2(x, ...)

cvtDataFrameFromJava2(x, thisClassName)
cvtDataFrameToJava2(x, ...)
matchDataFrameToJava2(x, ...)

cvtCharArrayFromJava2(x, thisClassName)
cvtCharArrayToJava2(x, ...)
matchCharArrayToJava2(x, ...)

cvtIntegerArrayFromJava2(x, thisClassName)
cvtIntegerArrayToJava2(x, ...)
matchIntegerArrayToJava2(x, ...)

cvtNumericArrayFromJava2(x, thisClassName)
cvtNumericArrayToJava2(x, ...)
matchNumericArrayToJava2(x, ...)

cvtLogicalArrayFromJava2(x, thisClassName)
cvtLogicalArrayToJava2(x, ...)
matchLogicalArrayToJava2(x, ...)

cvtRawArrayFromJava2(x, thisClassName)
cvtRawArrayToJava2(x, ...)
matchRawArrayToJava2(x, ...)

cvtComplexArrayFromJava2(x, thisClassName)
cvtComplexArrayToJava2(x, ...)
matchComplexArrayToJava2(x, ...)

cvtCharMatrixFromJava2(x, thisClassName)
cvtCharMatrixToJava2(x, ...)
matchCharMatrixToJava2(x, ...)

cvtIntegerMatrixFromJava2(x, thisClassName)
cvtIntegerMatrixToJava2(x, ...)
matchIntegerMatrixToJava2(x, ...)

cvtNumericMatrixFromJava2(x, thisClassName)
cvtNumericMatrixToJava2(x, ...)
matchNumericMatrixToJava2(x, ...)

cvtLogicalMatrixFromJava2(x, thisClassName)
cvtLogicalMatrixToJava2(x, ...)
matchLogicalMatrixToJava2(x, ...)

cvtRawMatrixFromJava2(x, thisClassName)
cvtRawMatrixToJava2(x, ...)
matchRawMatrixToJava2(x, ...)
```

```

cvtComplexMatrixFromJava2(x, thisClassName)
cvtComplexMatrixToJava2(x, ...)
matchComplexMatrixToJava2(x, ...)

cvtEnvFromJava2(x, thisClassName)
cvtEnvToJava2(x, ...)
matchEnvToJava2(x, ...)

cvtFileReferencesFromJava2(x, thisClassName)
cvtFileReferencesToJava2(x, ...)
matchFileReferencesToJava2(x, ...)

```

Arguments

`x` Either a reference to the Java object to be converted (e.g. `cvtArrayFromJava`), or a R object.

`...` Additional arguments passed to `SJava`

`thisClassName` Character representation of the class of the Java object that `x` refers to.

Details

The `cvt*` functions take an instance of an object of one language (R or Java) and convert it to an instance of the other language.

The `match*` functions take an instance of an object, and return a logical indicating whether the match criterion is satisfied.

The convention used in `RWebServices` is to name the functions as `<RObject>ToJava` or `<RObject>FromJava`.

`RWebServices` installs one of two types of converters. The the function `regAddonCvt` installs converters for the ‘object’ model, where R objects are represented in a hierarchy of Java objects that attempt to capture important attributes of the R instances. The mapping is as follows:

R	Java
raw	RRaw
logical	RLogical
character	RChar
integer	RInteger
numeric	RNumeric
complex	RComplex
list	RList
factor	RFactor
data.frame	RDataFrame
environment	REnvironment
array	RArray
matrix	RMatrix
‘other’	RUnknown

The ‘other’ converter is invoked when no other converter matches. `cvtUnknownToJava` creates an instance of the Java class `rservices.RUnknown` to hold the class, length, and string representation (i.e., the result of `print`) of the contents of the R object. `cvtUnknownFromJava` converts `rservices.RUnknown` instance to a R S4 instance if the original R object is a S4 instance, otherwise the function returns a list with the same class and length as the original R

object. This is likely to be very unsatisfactory.

The function `regAddonCvt2` installs converters for the ‘javalib’ model, where R objects are represented by Java primitive types where possible; NA values are not permitted. The mapping is as follows:

R	Java
raw	byte[]
logical	boolean[]
character	String[]
integer	int[]
numeric	double[]
complex	RJComplex
list	Object[]
factor	RJFactor
data.frame	RJDataFrame
environment	java.util.HashMap
‘*’Array,	RJ‘*’Array
‘*’Matrix,	RJ‘*’Matrix
FileReferences	RJFileReferences

The ‘*’Array and ‘*’Matrix and array entries represent instances of the `ArrayAndMatrix-class`, which provide strong type information about the `typeof` elements (raw, logical, character, integer, numeric, complex) in arrays and matrices.

Value

The `cvt*ToJava` functions return references to Java objects. The `cvt*FromJava` functions return instances of R objects. `match*` return TRUE when the match criterion is satisfied, FALSE otherwise.

Author(s)

Nianhua Li

References

<http://www.omegahat.org/RSJava/index.html>

See Also

`setJavaFunctionConverter`, `regAddonCvt`, `regAddonCvt2`

Description

`createMap` extracts type information from R function definitions, and uses this to create Java-style function calls with appropriately typed arguments. Types are then converted to Java objects.

A side effect is to create or modify a directory structure in the current working directory containing Java class information.

There are three methods defined:

`createMap(standardGeneric, missing, ...)` Intended to dispatch on S4 generics, creating maps for all currently visible methods.

`createMap(character, missing, ...)` Intended to dispatch on a character vector of function names, creating maps for each function.

`createMap(missing, pkgs=character, ...)` Intended to map all functions in `pkgs` with `typeInfo` applied. `pkgs` can be a character vector of package names, or in conjunction with the argument `splitPkgsToVector=TRUE` a comma-delimited list of packages. The latter behavior is meant to facilitate use with the `ant` command line, as `ant -Dpkg=caDNACopy,caPROcess gen-map-from-package`.

Usage

```
createMap(funcs, pkgs, generateTests = TRUE,
          outputDirectory = stop("specify outputDirectory"),
          typeMode = "javalib", deployMode = "jms",
          verbose = FALSE, ...)
## S4 method for signature 'missing,character':
createMap(funcs, pkgs, generateTests = TRUE,
          outputDirectory = stop("specify outputDirectory"),
          typeMode = "javalib", deployMode = "jms",
          verbose = FALSE, splitPkgsToVector=TRUE, ...,
          extraClasses=character())
```

Arguments

<code>funcs</code>	Function or list of functions with <code>typeInfo</code> already applied, or S4 generic method.
<code>pkgs</code>	Character string or vector of package names. Package namespaces are parsed for functions with <code>TypeInfo</code> , and R-Java maps are created for these.
<code>generateTests</code>	Logical. Should test code be generated?
<code>outputDirectory</code>	Directory where Java hierarchy will be created.
<code>typeMode</code>	Character, either "object" or "javalib". How Java objects should be generated; see generateDataMap and converters . <code>typemode</code> may be over-written by values in <code>system.file("rservices", "properties.R", package=pkg)</code> .
<code>deployMode</code>	Character, either "demo" or "jms". How the service will be deployed. "demo" is no longer supported.
<code>verbose</code>	Print information during mapping generation; useful for debugging.
<code>...</code>	Additional arguments, e.g., <code>S4DefaultTypedSig</code> used for providing type specifications for S4 functions when <code>funcs</code> is of class <code>standardGeneric</code> , or <code>splitPkgsToVector=TRUE</code> to treat <code>pkgs</code> as a comma-delimited list of packages.

`splitPkgsToVector`
 Parse character (1) `pkgs` as `split(pkgs, ", ")`, primarily for ant-based integration.

`extraClasses` A character vector of extra classes to map, in addition to those specified in the `TypeInfo` signature. `extraClasses` for this method are augmented by any classes defined in the file `system.file("rservices", "properties.R", package=pkg)`.

Details

`createMap` operates either on functions with `typeInfo` applied, or on S4 generic methods.

Some coercion occurs with `typeInfo` functions. All signatures have an explicit return type. `IndependentTypeSpecification` classes are 'expanded' to a complete set of typed signatures.

Function signatures for S4 methods are created from information used in generic method construction, supplemented by an optional default type signature supplied as a named argument `S4DefaultTypedSig`. Each method defined for a generic results in a Java signature. Arguments used for method dispatch are typed according to the dispatch rules for the function. Return types are determined by the `valueClass` of the generic (the `valueClass` of methods seem not to be defined, despite what the documentation indicates). Default values for other arguments, and for return values if `valueClass` is not used, can be created with a `TypedSignature` passed as a named argument `S4DefaultTypedSig`. Values implied by S4 method definitions override the defaults.

See `typeInfo2Java` for additional information on how conversion occurs.

Value

Primarily invokes for the side-effect of creating a Java class hierarchy reflecting the data and methods present in the call to `createMap`. Returns a list of Java signatures function definitions..

Author(s)

Martin Morgan <mtmorgan@fhcrc.org>

See Also

`createMap`, `missing`, `character-method`

Examples

```
library(RWebServices)

## S4
## Not run:
setClass("A", representation(x="character"))
setGeneric("foo", function(obj) standardGeneric("foo"))
setMethod("foo", "numeric", function(obj) new("A", x=as.character(obj)))
setMethod("foo", "character", function(obj) new("A", x=obj))

createMap(foo, outputDirectory=tempdir(), S4DefaultTypedSig=TypedSignature(returnType="A"
```

```
## End(Not run)
```

```
FileReferences-class  
  Class "FileReferences"
```

Description

FileReferences represents a collection of urls at which files can be referenced, the local names by which the files are to be referred to (to allow the file name portion of the url to differ from the name used to refer to the file), and the types (e.g., CEL, xls, etc.) of the files.

Objects from the Class

Objects can be created by calls to the constructor `FileReferences`. Objects are constructed with equal-length character vectors.

Elements can be accessed with `urls`, `localNames`, and `types`.

Slots

`urls`: Object of class "character" containing the urls where the files can be located

`localNames`: Object of class "character" containing the local names by which the files will be referred.

`types`: Object of class "character" containing information on the file 'type', for instance indicating that the files are CEL files (for gene expression analysis). Usually file types will be from a controlled vocabulary of types defined elsewhere.

Methods

See `FileReferences`

Author(s)

Martin Morgan mtmorgan@fhcrc.org

See Also

`FileReferences` for object construction, accessors `urls`, `localNames`, and `types`

Examples

```
showClass("FileReferences")  
FileReferences()
```

FileReferences *FileReferences constructor and accessors*

Description

Functions for creating and manipulating FileReferences-class objects.

Usage

```
FileReferences(urls = character(), localNames = basename(urls),
              types = character(length(urls)), ...)
urls(object, ...)
localNames(object, ...)
types(object, ...)
## S4 method for signature 'FileReferences':
length(x)
```

Arguments

urls	A character vector of urls of the files to be referenced. The urls are the actual locations of the files.
localNames	A (optional) character vector of local names of the files to be references. Local names are the names used to refer to the files internally, e.g., by functions wanting to use file names as a label for data frame rows. The length of the local names argument must match that of the urls; the default is to take the file name portion of the url as the local name.
types	A (optional) character vector of length equal to that of the urls, containing the type each file represents. Type might normally come from a controlled vocabulary; the default is a length zero character string, representing an unspecified type.
object	An object of class <code>FileReferences</code> , form which urls, local names, or types are to be extracted.
x	An object of class <code>FileReferences</code> , form which the length (number of file references) is to be determined.
...	Additional arguments, passed to the class initialization method or (currently) ignored by the accessors.

Value

FileReferences	Object of class <code>FileReferences</code> .
urls, localNames, types	character vector of urls, local names, or file types.
length	integer scalar of the number of references in the object.

Author(s)

Martin Morgan mtmorgan@fhcrc.org

See Also

[FileReferences](#)-class

Examples

```
obj <- FileReferences(c("/foo/bar", "/foo/baz"), type=rep("CEL", 2))
localNames(obj)
length(obj)
```

generateDataMap *Create java beans and mapping functions for a R data type*

Description

The `generateDataMap` function generates java beans and R–Java data type conversions for a R data type if they are not available in the environment `lookup`. All java mappings are output as files under `CurrentWorkingDir/biocJavaMap`, where `CurrentWorkingDir` is the result of `getwd()`. This function also updates environments `lookup` and `cvtImport` (see arguments below) as a side effect.

Usage

```
generateDataMap(rType, javaToR, deployMode, typeMode, lookup)
```

Arguments

<code>rType</code>	a character vector containing a R data type name. The data type is either a S4 class or a <code>ClassUnion</code> .
<code>javaToR</code>	logical, <code>TRUE</code> if want to convert Java data to R, <code>FALSE</code> if want to convert R data to Java.
<code>deployMode</code>	Character, either "demo" or "jms". How the service will be deployed. "demo" is no longer supported.
<code>typeMode</code>	Character, either "robject" or "javalib". How Java objects should be generated; see generateDataMap and converters
<code>lookup</code>	environment, key is <code>rType</code> , value is of type <code>RJMap</code> . <code>RJMap</code> provides the java type, java package, and java–R conversion function names for the key. By default, <code>lookup</code> only contains mapping information for vector, list, factor, data frame, array, matrix, environment and <code>NULL</code>

Value

returns updated environment `lookup`.

Author(s)

Nianhua Li

See Also

`printLookup`

Examples

```
## used internally
```

generateDataTest *Create a Java program to test R - Java data type mapping*

Description

The `generateDataTest` function is used to validate the results of function [generateDataMap](#). Given the name of a R data type, and the `lookup` environment updated by `generateDataMap`, function `generateDataTest` creates a test program in Java. The test program creates a java companion of the R data type, converts it to the R data type, and converts it back to Java. This round-trip can test both the Java bean and the convert functions.

Usage

```
generateDataTest(mainServ, mainPkg, lookup, addonType, verbose)
```

Arguments

<code>mainServ</code>	Name of web service; used to generate class name and properties files.
<code>mainPkg</code>	Package name, used in Java package hierarchy and usually the same as the R package name where the data object is defined.
<code>lookup</code>	environment containing mapping between R and Java types; see generateDataMap
<code>addonType</code>	character. Additional types required for creating the data test, e.g., to test conversion of an R <code>list</code> containing particular S4 classes requires that the particular classes be named as <code>addonType</code> .
<code>verbose</code>	logical. Report progress to console?

Value

returns NULL.

Author(s)

Nianhua Li

See Also

[generateDataMap](#)

Examples

```
## see '?generateDataMap' for an example of generating java test program
```

```
generateFunctionMap
```

Create java wrapper functions for a list of R functions

Description

The `generateFunctionMap` function generates java wrapper functions for a list of R functions. It also generates java beans and R–Java data type conversions for any R data types that are related to the function but unavailable in the environment `lookup`. This function also updates environments `lookup` and `cvtImport` (see arguments below) as a side effect.

Usage

```
generateFunctionMap(rTypeInfo, genTest = TRUE, workDir = getwd(),
  verbose = FALSE,
  deployModeName = "jms", typeModeName = "javalib",
  wsdlStyle = "WRAPPED", wsdlUse = "LITERAL",
  extraClasses = "", pkgRoot="org.bioconductor", ...)
```

Arguments

<code>rTypeInfo</code>	a list, each component is an instance of RJavaSignature-class and represents the signature of a R function.
<code>genTest</code>	logical, TRUE if want to generate a java program to test the java wrapper functions generated by <code>generateFunctionMap</code> , FALSE otherwise.
<code>workDir</code>	a character string, the path of the directory where this function generates all its outputs.
<code>verbose</code>	logical, TRUE if want to print out debug information, FALSE otherwise.
<code>deployModeName</code>	Character, either "demo" or "jms". How the service will be deployed. "demo" is no longer supported.
<code>typeModeName</code>	Character, either "robject" or "javalib". How Java objects should be generated; see generateDataMap and converters
<code>wsdlStyle</code>	Style of wsdl to create. A value of "WRAPPED" adds "_PortType" to the short name of the main service interface; all other values do not add "_PortType".
<code>wsdlUse</code>	Whether SOAP bindings are document/literal (value "LITERAL" or document/encoded (any other value). Only "LITERAL" is currently supported.
<code>extraClasses</code>	character. Extra classes required to convert function argument or return values, e.g., an argument of type <code>list</code> might require information about the classes present in the list. Usually this argument is not required, as S4 classes are parsed to their constituent parts
<code>pkgRoot</code>	character. Root package name of the java classes classes being created. It should be a sequence of one or more character strings delimited by dot, and no dot after the last string
<code>...</code>	Additional arguments, to be compatible with createMap .

Details

The java mappings generated under `workDir` are organized as following:

- `biocJavaMap` The base directory
- `biocJavaMap/package1` Java mappings for functions and data types defined in R `package1`
- `biocJavaMap/package1/data` Java beans and java <-> R mapping functions (in R) for data types defined in `package1`
- `biocJavaMap/package1/function` Java wrapper functions for functions defined in `package1`
- `biocJavaMap/package2` Java mappings for functions and data types defined in `package2`
- `biocJavaMap/mainService` Main java API, which invokes the java mapping functions for `package1`, `package2`, etc. `mainService` value is provided by user as input.

Value

A list, each component is an instance of `RJavaSignature-class` and represents the signature of a java wrapper function. The return value has a one-to-one mapping relation with input parameter `rTypeInfo`, i.e. the java wrapper function that is represented by the `ith` component in the return list, is the wrapper for the R function that is represented by the `ith` component in `rTypeInfo`.

Author(s)

Nianhua Li

Examples

```
## This function is usually invoked by createMap.
```

`getRSessionInfo` *Report R session information in a web-services friendly format.*

Description

This function has `TypeInfo` applied, and so is mapped as a web service in the `org.bioconductor.packages.rservices` name space.

Usage

```
getRSessionInfo(verbose = FALSE)
```

Arguments

`verbose` A `logical(1)`, with `FALSE` returning a character vector of packages with (for non-base packages) version number appended and `TRUE` returning a character vector capturing the output of `sessionInfo()`.

Value

A character vector containing information on all attached and loaded packages in the current R session.

Author(s)

Martin Morgan mtmorgan@fhcrc.org

Examples

```
getRSessionInfo(FALSE)
```

```
register-converters
```

Load R - Java data converters.

Description

When invoking R from Java, data type conversions between R and Java are handled by `SJava`. But `SJava` only supports conversions for limited R data types, the conversions for other R data types are specified by user converters and interpreted by `SJava`. `regAddonCvt` and `regTestCvt` help to load user converters.

Usage

```
regAddonCvt ()  
regAddonCvt2 ()  
regTestCvt ()
```

Details

These functions are usually used by the auto-generated codes from [generateFunctionMap](#). Users do not need to deal with them. `regAddonCvt` and `regAddonCvt2` load converters for R character, logical, integer, numeric, raw, complex, array, matrix, data.frame, list, environment, and factor. The `regAddonCvt` converters follow the ‘robject’ model whereas `regAddonCvt2` follows the ‘javalib’ model; see [converters](#) for more information. `regTestCvt` are used for low-level testing.

Author(s)

Nianhua Li

```
printLookup
```

Print R-Java data type mapping information

Description

`printLookup` prints the R-Java data type mapping information.

Usage

```
printLookup(lookup, all = TRUE)
```


Arguments

lookup	environment, the environment contains the R-Java data type mapping information. It is generated by <code>generateDataMap</code> .
all	logical, FALSE to just print the mappings for user-defined data types, TRUE to print the mappings for basic R data types as well.

Author(s)

Nianhua Li

Examples

```
# please try the example under examples/s4Map
```

```
retrieve-methods    Retrieve file references from remote locations
```

Description

This method retrieve files referenced by its first argument to locations determined by its second argument. The return value is a `FileReferences` object summarizing the destination.

Usage

```
retrieve(from, to, ...)
```

Arguments

from	The source from which objects will be retrieved; typically (or exclusively, depending on method) 'remote' locations accessible via, e.g., http.
to	The destination to which files will be copied; typically on the local file system.
...	Additional arguments, passed to the function performing the download.

Methods

from = "FileReferences", to = "character" from contains remote urls; files must be retrievable using `getBinaryURL` from the `RCurl` package. ... arguments are passed to `getBinaryURL`. to is a directory name to which files will be copied; the directory is created if it does not exist. File names will be unique.

from = "FileReferences", to = "FileReferences" from is as in `retrieve, FileReferences, character-method`. to specifies destination urls; `urls(to)` must have the same number of elements as `urls{from}`, must not already exist on the local file system, and must not require creation of new directories. `localNames` and `types` of to are replaced by corresponding elements from from.

from = "FileReferences", to = "missing" from is as in the `retrieve, FileReferences, character-method`. The destination is created using `tempfile()`, and forwarding this as the second argument to `retrieve, FileReferences, character-method`. The effect is to retrieve files to R's temporary directory; these files will be removed when the R session ends.

Examples

```

try({ # fails when no internet available
  from <- FileReferences(c("http://bioconductor.org/biocLite.R",
                          "http://bioconductor.org/index.html"))
  ## to R's temporary directory
  to <- retrieve(from)
  urls(to)
  localNames(to)

  ## tell R where to copy files to
  toDir <- tempfile()
  dir.create(toDir, recursive=TRUE)
  toUrls <- file.path(toDir, localNames(from))
  retrieve(from, FileReferences(toUrls))
  list.files(toDir)
})

```

RJavaPkgFunctions-class

Java signatures derived from R methods

Description

Class RJavaPkgFunctions contains elements of Java signatures, including the source R package, the corresponding java class, and type information about the Java function.

Create this class using [createMap](#) or [generateFunctionMap](#).

Slots

`rPackage` Character vector of R source packages
`javaClass` Character vector of corresponding Java classes
`javaTypeInfo` List of Java function signatures.

Author(s)

MT Morgan <mtmorgan@fhcrc.org>

See Also

[generateFunctionMap](#), [createMap](#)

Examples

```

library(RWebServices)

oneWayAnova <- function( response, predictor ) {
  if ( is.character( predictor ) )
    return( oneWayAnova( response, as.factor( predictor ) ) )
  formula <- as.formula( substitute( response ~ predictor ) )
  result <- lm( formula )
  anova( result )
}

```

```

typeInfo(oneWayAnova) <-
  SimultaneousTypeSpecification(
    TypedSignature(
      response = "numeric",
      predictor = "factor"),
    TypedSignature(
      response = "numeric",
      predictor = "character"),
    returnType = "anova" )

## Not run:
res <- createMap("oneWayAnova", outputDirectory=tempdir(),
typeMode="robject", verbose=TRUE)

## End(Not run)

```

RJavaSignature-class

String representations of R type signatures from R functions

Description

Class "RJavaSignature" contains elements of java-style function signature, including return type, function name, and argument names/types

Create this class using [typeInfo2Java](#).

Slots

returnType Character string describing the return type of the function. This must be defined.

funcName: Function name as character string.

args: Vector of character strings providing argument types. Argument names are stored as name attributes.

Author(s)

MT Morgan <mtmorgan@fhcrc.org>

See Also

[link{typeInfo2Java}](#)

Examples

```

library(RWebServices)

oneWayAnova <- function( response, predictor ) {
  if ( is.character( predictor ) )
    return( oneWayAnova( response, as.factor( predictor ) ) )
  formula <- as.formula( substitute( response ~ predictor ) )
  result <- lm( formula )
  anova( result )
}

```

```
typeInfo(oneWayAnova) <-  
  SimultaneousTypeSpecification(  
    TypedSignature(  
      response = "numeric",  
      predictor = "factor"),  
    TypedSignature(  
      response = "numeric",  
      predictor = "character"),  
    returnType = "anova" )  
  
res <- typeInfo2Java(oneWayAnova)  
  
res  
  
summary(res)
```

RWebServices-package

Expose R functions as web services through Java/Axis/Apache

Description

This package provides mechanisms for automatic function prototyping and exposure of R functionality in a web services environment.

Details

Package:	RWebServices
Type:	Package
Version:	1.0
Date:	2005-12-23
License:	What license is it under?

Author(s)

Written by Nianhua Li, MT Morgan. Maintainer: Robert Gentleman <rgentle@fhcrc.org>

See Also

The `TypeInfo` package.

SinkOutput-class *Results captured by calls to sinkSetup and sinkRetrieve*

Description

Create this class using [sinkSetup](#) and [sinkRetrieve](#). A typical use is to wrap function evaluation calls in such a way as to redirect screen output to character variables.

Slots

`stdout` Vector of type character containing each line of output destined for the 'console', excepting error and warning messages. Each element in the vector is a 'line' of string output, as determined by R.

`stderr`: As with `stdout`, but capturing warning and error messages

Author(s)

MT Morgan <mtmorgan@fhcrc.org>

See Also

[link{sinkSetup}](#), [sinkRetrieve](#)

Examples

```
library(RWebServices)

sinkSetup()
ls()
try( fails() )
f <- function() stop("fails in function f")
try( f() )
sinkRetrieve()
```

`sinkSetup`, `sinkRetrieve`
Capture and retrieve screen output

Description

`sinkSetup` establishes temporary files to capture output that would normally be directed toward the screen, and redirects both standard and error output to these files. `sinkRetrieve` retrieves the output, and removes screen redirections so output again appears on the screen.

Usage

```
sinkSetup()
sinkRetrieve()
```

Details

These functions are used to redirect and then retrieve screen output. Redirection is to objects created with `file`, with no arguments (i.e., a temporary file, unlinked from the file system). Both standard output and error output are redirected.

User-level calls of `sink` between calls to `sinkSetup` and `sinkRetrieve` may confuse screen (especially error) capture, likely resulting in warnings when `sinkRetrieve` is called.

Value

`sinkRetrieve` returns an object of `SinkOutput-class`, the slots of which contain vectors of the lines of text directed toward the screen.

Author(s)

MT Morgan

Examples

```
library(RWebServices)

sinkSetup()
ls()
try( fails() )
f <- function() stop("fails in function f")
try( f() )
sinkRetrieve()
```

Test utilities

Utilities for facilitating data and method tests

Description

These functions provide utilities that are useful when testing different aspects of R / Java communication.

Usage

```
checkJava2R(javaData, rVariable)
checkPkgVersion(pkgName, expVersion)
reflectObj(x, verbose=FALSE)
```

Arguments

<code>javaData</code>	Object translated from Java
<code>rVariable</code>	R variable containing an instance that is supposed to be identical to <code>javaData</code> . <code>rVariable</code> might have been created in previous calls, or loaded from a data file.
<code>pkgName</code>	Name of package whose version will be determined.
<code>expVersion</code>	Character string with expected package version.
<code>x</code>	Object to be returned to Java.
<code>verbose</code>	Logical, indicating whether R reports information about the object.

Value

`checkJava2R` returns TRUE if `javaData` is identical to `rVariable`, or signals an error otherwise.

`checkPkgVersion` returns true if the installed package matches the expected package, or signals a warning otherwise.

`reflectObj` returns the object.

Author(s)

Nianhua Li

<code>typeInfo2Java</code>	<i>Create Java-like function signatures from R functions</i>
----------------------------	--

Description

The `typeInfo2Java` methods convert functions or `TypeInfo` structures to a Java-like signature, without coercion to Java types. See `createMap` to convert functions and coerce arguments.

These functions are primarily for internal use.

Usage

```
typeInfo2Java(x, ...)
```

Arguments

<code>x</code>	function with <code>TypeInfo</code> already applied, S4 function, or any <code>TypeInfo</code> class.
<code>...</code>	Additional arguments specific to different methods. These are usually <code>funcName</code> (the name of the function) or <code>args</code> (a list of argument names)

Details

`TypeInfo` offers greater flexibility in type specification than can easily be implemented in Java. This function fails with `DynamicTypeTest`, and treats `StrictIsTypeTest` as `InheritsTypeTest` (issuing a warning in the process). See `NamedTypeTest-class` of `TypeInfo` for more information.

Value

An object of `RJavaSignature-class`, containing return type, function name, and argument type/name as slots with named character vectors.

Author(s)

MT Morgan

Examples

```

library(RWebServices)

func <- function( response, predictor ) {
  if ( is.character( predictor ) )
    return( oneWayAnova( response, as.factor( predictor ) ) )
  formula <- as.formula( substitute( response ~ predictor ) )
  result <- lm( formula )
  anova( result )
}

## this indirection makes it easier to apply typeInfo
oneWayAnova <- func

typeInfo(oneWayAnova) <-
  SimultaneousTypeSpecification(
    TypedSignature(
      response = "numeric",
      predictor = "factor"),
    returnType = "anova" )

typeInfo2Java(oneWayAnova)

oneWayAnova <- func

typeInfo(oneWayAnova) <-
  SimultaneousTypeSpecification(
    TypedSignature(
      response = "numeric",
      predictor = "factor"),
    TypedSignature(
      response = "numeric",
      predictor = "character"),
    returnType = "anova" )

typeInfo2Java(oneWayAnova)

oneWayAnova <- func

typeInfo(oneWayAnova) <-
  IndependentTypeSpecification(
    response = c("numeric"),
    predictor = c( "factor", "character", "numeric" ),
    returnType = "anova"
  )

typeInfo2Java(oneWayAnova)

oneWayAnova <- func

typeInfo(oneWayAnova) <-
  SimultaneousTypeSpecification(
    TypedSignature(
      response = "numeric",
      predictor = "factor",

```



```

        returnType = "matrix"),
    TypedSignature(
      response = "numeric",
      predictor = "character"),
    returnType = "anova" )

typeInfo2Java(oneWayAnova)

oneWayAnova <- func

typeInfo(oneWayAnova) <-
  IndependentTypeSpecification(
    response = c("numeric"),
    predictor = c( "factor", "character", "numeric" ),
    returnType = c("anova")
  )

typeInfo2Java(oneWayAnova)

# Warning about StrictIsTypeTest
oneWayAnova <- func
typeInfo(oneWayAnova) <-
  IndependentTypeSpecification(
    response = StrictIsTypeTest("numeric"),
    predictor = c( "factor", "character", "numeric" ),
    returnType = c("anova")
  )
typeInfo2Java(oneWayAnova)

oneWayAnova <- func
typeInfo(oneWayAnova) <-
  IndependentTypeSpecification(
    response = "numeric",
    predictor = quote( ( length(predictor) == length(response)) && is( predictor, "factor" ) ),
    returnType = c("anova")
  )
typeInfo2Java(oneWayAnova)

```

unpackAntScript *Unpack script for building, testing, and installing packages.*

Description

RWebServices includes a number of scripts and files to be used to develop, test, and deploy services. This function unpacks a 'master' script and partly configured properties files to a convenient directory location.

Usage

```
unpackAntScript(toDir = stop("specify destination directory for unpacking"), overwrite = TRUE)
```

Arguments

toDir	Destination (top-level) directory. Warnings are issued if files already exist.
overwrite	Overwrite output?

Value

This function is used for its side effect.

Author(s)

Martin Morgan <mtmorgan@fhcrc.org>

Examples

```
## Not run: unpackAntScript("/tmp/ants")
## Not run:
## From the command line
echo "library(RWebServices); unpackAntScript('~tmp/ants')" | R --vanilla

## End(Not run)
```

Index

*Topic classes

- ArrayAndMatrix-class, 1
- FileReferences-class, 10
- RJavaPkgFunctions-class, 18
- RJavaSignature-class, 19
- SinkOutput-class, 21

*Topic documentation

- createMap, 7
- sinkSetup, sinkRetrieve, 21
- typeInfo2Java, 23

*Topic interface

- converters, 3
- generateDataMap, 12
- generateDataTest, 13
- generateFunctionMap, 14
- printLookup, 16
- register-converters, 16

*Topic manip

- FileReferences, 11
- getRSessionInfo, 15
- unpackAntScript, 25

*Topic methods

- retrieve-methods, 17

*Topic package

- RWebServices-package, 20

*Topic programming

- createMap, 7
- sinkSetup, sinkRetrieve, 21
- Test utilities, 22
- typeInfo2Java, 23

array, 1

ArrayAndMatrix-class, 7

ArrayAndMatrix-class, 1

CharArray (ArrayAndMatrix-class),
1

CharArray-class
(ArrayAndMatrix-class), 1

CharMatrix
(ArrayAndMatrix-class), 1

CharMatrix-class
(ArrayAndMatrix-class), 1

checkJava2R (Test utilities), 22

checkPkgVersion (Test utilities),
22

ComplexArray
(ArrayAndMatrix-class), 1

ComplexArray-class
(ArrayAndMatrix-class), 1

ComplexMatrix
(ArrayAndMatrix-class), 1

ComplexMatrix-class
(ArrayAndMatrix-class), 1

converters, 3, 8, 12, 14, 16

createMap, 1, 7, 14, 18, 23

createMap, character, missing-method
(createMap), 7

createMap, missing, character-
method,
9

createMap, missing, character-method
(createMap), 7

createMap, standardGeneric, missing-method
(createMap), 7

cvtArrayFromJava (converters), 3

cvtArrayToJava (converters), 3

cvtCharacterFromJava
(converters), 3

cvtCharacterToJava (converters), 3

cvtCharacterToJava2 (converters),
3

cvtCharArrayFromJava2
(converters), 3

cvtCharArrayToJava2 (converters),
3

cvtCharMatrixFromJava2
(converters), 3

cvtCharMatrixToJava2
(converters), 3

cvtComplexArrayFromJava2
(converters), 3

cvtComplexArrayToJava2
(converters), 3

cvtComplexFromJava (converters), 3

cvtComplexFromJava2 (converters),
3

- cvtComplexMatrixFromJava2
(*converters*), 3
- cvtComplexMatrixToJava2
(*converters*), 3
- cvtComplexToJava (*converters*), 3
- cvtComplexToJava2 (*converters*), 3
- cvtDataFrameFromJava
(*converters*), 3
- cvtDataFrameFromJava2
(*converters*), 3
- cvtDataFrameToJava (*converters*), 3
- cvtDataFrameToJava2 (*converters*), 3
- cvtEnvFromJava (*converters*), 3
- cvtEnvFromJava2 (*converters*), 3
- cvtEnvToJava (*converters*), 3
- cvtEnvToJava2 (*converters*), 3
- cvtFactorFromJava (*converters*), 3
- cvtFactorFromJava2 (*converters*), 3
- cvtFactorToJava (*converters*), 3
- cvtFactorToJava2 (*converters*), 3
- cvtFileReferencesFromJava
(*converters*), 3
- cvtFileReferencesFromJava2
(*converters*), 3
- cvtFileReferencesToJava
(*converters*), 3
- cvtFileReferencesToJava2
(*converters*), 3
- cvtIntegerArrayFromJava2
(*converters*), 3
- cvtIntegerArrayToJava2
(*converters*), 3
- cvtIntegerFromJava (*converters*), 3
- cvtIntegerMatrixFromJava2
(*converters*), 3
- cvtIntegerMatrixToJava2
(*converters*), 3
- cvtIntegerToJava (*converters*), 3
- cvtIntegerToJava2 (*converters*), 3
- cvtListFromJava (*converters*), 3
- cvtListToJava (*converters*), 3
- cvtListToJava2 (*converters*), 3
- cvtLogicalArrayFromJava2
(*converters*), 3
- cvtLogicalArrayToJava2
(*converters*), 3
- cvtLogicalFromJava (*converters*), 3
- cvtLogicalMatrixFromJava2
(*converters*), 3
- cvtLogicalMatrixToJava2
(*converters*), 3
- cvtLogicalToJava (*converters*), 3
- cvtLogicalToJava2 (*converters*), 3
- cvtMatrixFromJava (*converters*), 3
- cvtMatrixToJava (*converters*), 3
- cvtNumericArrayFromJava2
(*converters*), 3
- cvtNumericArrayToJava2
(*converters*), 3
- cvtNumericFromJava (*converters*), 3
- cvtNumericMatrixFromJava2
(*converters*), 3
- cvtNumericMatrixToJava2
(*converters*), 3
- cvtNumericToJava (*converters*), 3
- cvtNumericToJava2 (*converters*), 3
- cvtRawArrayFromJava2
(*converters*), 3
- cvtRawArrayToJava2 (*converters*), 3
- cvtRawFromJava (*converters*), 3
- cvtRawMatrixFromJava2
(*converters*), 3
- cvtRawMatrixToJava2 (*converters*), 3
- cvtRawToJava (*converters*), 3
- cvtRawToJava2 (*converters*), 3
- cvtUnknownFromJava (*converters*), 3
- cvtUnknownToJava (*converters*), 3
- cvtVectorFromJava (*converters*), 3
- cvtVectorToJava (*converters*), 3
- file, 22
- FileReferences, 10, 11, 11, 12, 17
- FileReferences-class, 10
- generateDataMap, 8, 12, 12–14, 17
- generateDataTest, 13
- generateFunctionMap, 14, 16, 18
- getRSessionInfo, 15
- IndependentTypeSpecification, 9
- IntegerArray
(*ArrayAndMatrix-class*), 1
- IntegerArray-class
(*ArrayAndMatrix-class*), 1
- IntegerMatrix
(*ArrayAndMatrix-class*), 1
- IntegerMatrix-class
(*ArrayAndMatrix-class*), 1
- length, FileReferences-method
(*FileReferences*), 11
- localNames, 10
- localNames (*FileReferences*), 11

- LogicalArray
 - (ArrayAndMatrix-class), 1
- LogicalArray-class
 - (ArrayAndMatrix-class), 1
- LogicalMatrix
 - (ArrayAndMatrix-class), 1
- LogicalMatrix-class
 - (ArrayAndMatrix-class), 1
- matchArrayToJava (converters), 3
- matchCharacterToJava
 - (converters), 3
- matchCharacterToJava2
 - (converters), 3
- matchCharArrayToJava2
 - (converters), 3
- matchCharMatrixToJava2
 - (converters), 3
- matchComplexArrayToJava2
 - (converters), 3
- matchComplexMatrixToJava2
 - (converters), 3
- matchComplexToJava (converters), 3
- matchComplexToJava2 (converters), 3
- matchDataFrameToJava
 - (converters), 3
- matchDataFrameToJava2
 - (converters), 3
- matchEnvToJava (converters), 3
- matchEnvToJava2 (converters), 3
- matchFactorToJava (converters), 3
- matchFactorToJava2 (converters), 3
- matchFileReferencesToJava
 - (converters), 3
- matchFileReferencesToJava2
 - (converters), 3
- matchIntegerArrayToJava2
 - (converters), 3
- matchIntegerMatrixToJava2
 - (converters), 3
- matchIntegerToJava (converters), 3
- matchIntegerToJava2 (converters), 3
- matchListToJava (converters), 3
- matchListToJava2 (converters), 3
- matchLogicalArrayToJava2
 - (converters), 3
- matchLogicalMatrixToJava2
 - (converters), 3
- matchLogicalToJava (converters), 3
- matchLogicalToJava2 (converters), 3
- matchMatrixToJava (converters), 3
- matchNumericArrayToJava2
 - (converters), 3
- matchNumericMatrixToJava2
 - (converters), 3
- matchNumericToJava (converters), 3
- matchNumericToJava2 (converters), 3
- matchRawArrayToJava2
 - (converters), 3
- matchRawMatrixToJava2
 - (converters), 3
- matchRawToJava (converters), 3
- matchRawToJava2 (converters), 3
- matchUnknownToJava (converters), 3
- matchVectorToJava (converters), 3
- matrix, 1
- NamedTypeTest-class, 23
- NumericArray
 - (ArrayAndMatrix-class), 1
- NumericArray-class
 - (ArrayAndMatrix-class), 1
- NumericMatrix
 - (ArrayAndMatrix-class), 1
- NumericMatrix-class
 - (ArrayAndMatrix-class), 1
- printLookup, 16
- RawArray (ArrayAndMatrix-class), 1
- RawArray-class
 - (ArrayAndMatrix-class), 1
- RawMatrix (ArrayAndMatrix-class), 1
- RawMatrix-class
 - (ArrayAndMatrix-class), 1
- reflectObj (Test utilities), 22
- regAddonCvt, 6, 7
- regAddonCvt
 - (register-converters), 16
- regAddonCvt2, 7
- regAddonCvt2
 - (register-converters), 16
- register-converters, 16
- regTestCvt (register-converters), 16
- retrieve (retrieve-methods), 17
- retrieve, FileReferences, character-method
 - (retrieve-methods), 17
- retrieve, FileReferences, FileReferences-method
 - (retrieve-methods), 17

- retrieve, FileReferences, missing-method
 - (*retrieve-methods*), 17
- retrieve-methods, 17
- RJavaPkgFunctions-class, 18
- RJavaSignature-class, 14, 15, 23
- RJavaSignature-class, 19
- RWebServices
 - (*RWebServices-package*), 20
- RWebServices-package, 20

- setJavaFunctionConverter, 7
- show, RJavaPkgFunctions-method
 - (*RJavaPkgFunctions-class*), 18
- show, RJavaSignature-method
 - (*RJavaSignature-class*), 19
- sink, 22
- SinkOutput-class, 22
- SinkOutput-class, 21
- sinkRetrieve, 21
- sinkRetrieve (*sinkSetup*, *sinkRetrieve*), 21
- sinkSetup, 21
- sinkSetup (*sinkSetup*, *sinkRetrieve*), 21
- sinkSetup, sinkRetrieve, 21

- Test utilities, 22
- TypedSignature, 9
- typeInfo, 9
- typeInfo2Java, 9, 19, 23
- typeInfo2Java, ANY-method
 - (*typeInfo2Java*), 23
- typeInfo2Java, character-method
 - (*typeInfo2Java*), 23
- typeInfo2Java, DynamicTypeTest-method
 - (*typeInfo2Java*), 23
- typeInfo2Java, function-method
 - (*typeInfo2Java*), 23
- typeInfo2Java, genericFunction-method
 - (*typeInfo2Java*), 23
- typeInfo2Java, IndependentTypeSpecification-method
 - (*typeInfo2Java*), 23
- typeInfo2Java, InheritsTypeTest-method
 - (*typeInfo2Java*), 23
- typeInfo2Java, list-method
 - (*typeInfo2Java*), 23
- typeInfo2Java, SimultaneousTypeSpecification-method
 - (*typeInfo2Java*), 23
- typeInfo2Java, standardGeneric-method
 - (*typeInfo2Java*), 23
- typeInfo2Java, StrictIsTypeTest-method
 - (*typeInfo2Java*), 23
- typeInfo2Java, TypedSignature-method
 - (*typeInfo2Java*), 23
- types, 10
- types (*FileReferences*), 11
- unpackAntScript, 25
- urls, 10
- urls (*FileReferences*), 11